

DEFY ADVANCED PRO 1

GIANT



ESPECIFICACIONES

| CUADRO | |
|----------------------|--|
| TALLAS | XS, S, M, M/L, L, XL |
| COLORES | White/Iris |
| CUADRO | Advanced-grade Composite, 12x142mm thru-axle, disc |
| HORQUILLA | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| AMORTIGUADOR | N/A |
| COMPONENTES | |
| MANILLAR | Giant Contact SL D-Fuse XS:410/380mm, S:410/380mm, M:430/400mm, M/L:430/400mm, L:450/420mm, XL:450/420mm |
| PUÑOS | Stratus Lite 3.0 |
| POTENCIA | Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm |
| TIJA DE SILLÍN | Giant D-Fuse SL, composite, -5/+15mm offset |
| SILLÍN | Giant Fleet SL |
| TRANSMISIÓN | |
| MANETAS DE CAMBIO | SRAM Rival AXS E1 |
| DESVIADOR | SRAM Rival AXS E1 |
| CAMBIO TRASERO | SRAM Rival AXS E1 |
| FRENOS | SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm |
| PALANCAS DE FRENOS | SRAM Rival AXS E1 hydraulic |
| CASSETTE | SRAM Rival, 12-speed, 10x36 |
| CADENA | SRAM Rival E1 |
| JGO. PLATOS Y BIELAS | SRAM Rival E1 DUB, 33/46 with Quark power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm |
| CAJA DE PEDALIER | SRAM DUB, press fit |

| RUEDAS | |
|-----------------------------|--|
| LLANTAS | Giant SLR 1 40 Carbon Disc WheelSystem |
| BUJES | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle |
| RADIOS | Sapim |
| CUBIERTAS | Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding |
| EXTRAS | computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size |
| LÍMITES | |
| MÁXIMA ANCHURA DE NEUMÁTICO | 40mm |

Precio: 5.099,00 €

GEOMETRÍA

| CUADRO | XS | S | M | ML | L | XL |
|--|-------|-------|-------|-------|-------|-------|
| Longitud del tubo del sillín (mm) | 410 | 445 | 480 | 515 | 535 | 565 |
| Ángulo del tubo del sillín | 74,5° | 74,0° | 73,5° | 73,0° | 73,0° | 73,0° |
| Longitud del tubo superior (mm) (mm) | 515 | 530 | 545 | 560 | 575 | 595 |
| Longitud del tubo de dirección (mm) (mm) | 125 | 135 | 150 | 175 | 195 | 215 |
| Ángulo del tubo de dirección | 70,5° | 71,8° | 72,5° | 72,5° | 72,5° | 72,5° |
| Inclinación de la horquilla (mm) | 50 | 50 | 50 | 50 | 50 | 50 |
| Trail (mm) (mm) | 71,6 | 63,4 | 58,6 | 58,6 | 58,6 | 58,6 |
| Distancia entre ejes (mm) (mm) | 995 | 994 | 998 | 1010 | 1025 | 1040 |
| Longitud de la vaina (mm) (mm) | 420 | 420 | 420 | 420 | 420 | 420 |
| Caída del eje de pedalier (mm) (mm) | 75 | 75 | 75 | 70 | 70 | 70 |
| Stack (mm) (mm) | 527 | 541 | 558 | 577 | 596 | 615 |
| Reach (mm) (mm) | 369 | 375 | 380 | 384 | 393 | 402 |
| Altura del suelo al tubo (mm) (mm) | 705 | 733 | 762 | 796 | 814 | 841 |
| Ancho del manillar (mm) (mm) | 404 | 404 | 424 | 424 | 444 | 444 |
| Longitud de la potencia (mm) (mm) | 80 | 90 | 100 | 100 | 110 | 110 |
| Longitud de las bielas (mm) (mm) | 165 | 165 | 170 | 170 | 172,5 | 172,5 |

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.