

DEFY ADVANCED PRO 1



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, M/L, L, XL
VÄRIT	Midnight Moon
RUNKO	Advanced-grade Composite, 12x142mm thru-axle, disc
HAARUKKA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMONENTIT	
OHJAUSTANKO	Giant Contact SL D-Fuse XS:410/380mm, S:410/380mm, M:430/400mm, M/L:430/400mm, L:450/420mm, XL:450/420mm
GRIPIT	Stratus Lite 3.0
OHJAINKANNATIN	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SATULATOLPPA	Giant D-Fuse SL, composite, 16mm offset
SÄTULA	Giant Fleet SL
VOIMANSIIRTO	
VAIHDEVIPU	SRAM Rival AXS E1
ETUVAIHTAJA	SRAM Rival AXS E1
TAKAVAIHTAJA	SRAM Rival AXS E1
JARRUT	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
JARRUKAHVAT	SRAM Rival AXS E1 hydraulic
RATASPAKKA	SRAM Rival, 12-speed, 10x36
KETJUT	SRAM Rival E1
KAMPISARJA	SRAM Rival E1 DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant SLR 1 40 Carbon Disc WheelSystem
NAVAT	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
PINNAT	Sapim
RENKAAT	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
LISÄTIEDOT	computer mount, fender mount, water bottle cages, tubeless prepared
RAJOITTEET	
MAX RENGASVARA	40mm

Suositusinta: 5 529,00 €

GEOMETRIA

RUNKO	S	M	ML	L	XL
Satulaputken pituus (mm)	445	480	515	535	565
Satulatolpan asennussyvyys (mm)	190	190	190	190	190
Satulaputken kulma	74,0°	73,5°	73,0°	73,0°	73,0°
Vaakaputken pituus (mm)	530	545	560	575	595
Emäputken pituus (mm)	135	150	175	195	215
Emäputken kulma	71,8°	72,5°	72,5°	72,5°	72,5°
Haarukan offset (mm)	50	50	50	50	50
Trail-mitta (mm)	63,4	58,6	58,6	58,6	58,6
Akseliväli (mm)	994	998	1010	1025	1040
Takahaarukan alaputken pituus (mm)	420	420	420	420	420
Keskiön pudotus (mm)	75	75	70	70	70
Stack-mitta (mm)	541	558	577	596	615
Reach-mitta (mm)	375	380	384	393	402
Standover-mitta (mm)	733	762	796	814	841
Ohjaustangon leveys (mm)	404	424	424	444	444
Ohjainkannattimen pituus (mm)	90	100	100	110	110
Kammen pituus (mm)	165	170	170	172,5	172,5

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.