



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COULEURS	White/Iris
CADRE	Advanced-grade Composite, 12x142mm thru-axle, disc
FOURCHE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTISSEUR (SHOCK)	N/A
COMPOSANTES	
GUIDON	Giant Contact SL D-Fuse
POIGNÉES	Stratus Lite 3.0
POTENCE	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
TIGE DE SELLE	Giant D-Fuse SL, composite, -5/+15mm offset
SELLE	Giant Fleet SL
TRANSMISSION (DRIVETRAIN)	
LEVIERS DE VITESSE	SRAM Rival AXS E1
DÉRAILLEUR AVANT	SRAM Rival AXS E1
DÉRAILLEUR ARRIÈRE	SRAM Rival AXS E1
FREINS	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
LEVIERS DE FREIN	SRAM Rival AXS E1 hydraulic
CASSETTE	SRAM Rival, 12-speed, 10x36
CHAÎNE	SRAM Rival E1
PÉDALIER	SRAM Rival E1 DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOÎTIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant SLR 1 40 Carbon Disc WheelSystem
MOYEUX	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Sapim
PNEUS	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
EXTRAS	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
LIMITES	
MAX TIRE CLEARANCE	40mm

Prix de détail: 6 699,00 \$

GÉOMÉTRIE

CADRE	XS	S	M	ML	L	XL
Longueur du tube de selle (mm)	410	445	480	515	535	565
Angle du tube de selle	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Longueur du tube supérieur (top tube) (mm)	515	530	545	560	575	595
Longueur du tube de direction (head tube) (mm)	125	135	150	175	195	215
Angle du tube de direction	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Déport (rake) de fourche (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Empattement (mm)	995	994	998	1010	1025	1040
Longueur des bases (mm)	420	420	420	420	420	420
Hauteur du boîtier de pédalier (mm)	75	75	75	70	70	70
Portée Verticale (Stack) (mm)	527	541	558	577	596	615
Portée Horizontale (Reach) (mm)	369	375	380	384	393	402
Hauteur du cadre (mm)	705	733	762	796	814	841
Largeur du Guidon (mm)	404	404	424	424	444	444
Longueur de la Potence (mm)	80	90	100	100	110	110
Longueur des manivelles (mm)	165	165	170	170	172,5	172,5

GIANT Canada se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.