

DEFY ADVANCED PRO 1



SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, M/L, L, XL
BOJE	White/Iris
OKVIR	Advanced-grade Composite, 12x142mm thru-axle, disc
VILICA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
VOLAN	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPS	Stratus Lite 3.0
LULA VOLANA	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
CIJEV SJEDALA	Giant D-Fuse SL, composite, -5/+15mm offset
SJEDALO	Giant Fleet SL
POGON	
RUČICE MJENJAČA	SRAM Rival AXS E1
PREDNJI MJENJAČ	SRAM Rival AXS E1
STRAŽNJI MJENJAČ	SRAM Rival AXS E1
KOČNICE	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
RUČICE KOČNICA	SRAM Rival AXS E1 hydraulic
KAZETA	SRAM Rival, 12-speed, 10x36
LANAC	SRAM Rival E1
POGON	SRAM Rival E1 DUB, 33/46 with Quark power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant SLR 1 40 Carbon Disc WheelSystem
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
ŽBICE	Sapim
GUME	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
DODACI	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dužina cijevi sjedala (mm)	410	445	480	515	535	565
Kut cijevi sjedala	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Dužina gornje cijevi (mm)	515	530	545	560	575	595
Dužina prednje cijevi (mm)	125	135	150	175	195	215
Kut vilice	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Zakrivljenost vilice (offset) (mm)	50	50	50	50	50	50
Staza (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Međuosovinski razmak kotača (mm)	995	994	998	1010	1025	1040
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	420	420	420	420	420	420
Položaj osovine pogona (mm)	75	75	75	70	70	70
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	527	541	558	577	596	615
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	369	375	380	384	393	402
Prekoračna visina (mm)	705	733	762	796	814	841
Širina volana (mm)	404	404	424	424	444	444
Dužina lule volana (mm)	80	90	100	100	110	110
Dužina poluge pedale (mm)	165	165	170	170	172,5	172,5

Sve navedene specifikacije podložne su promjeni bez prethodne najave.