

DEFY ADVANCED PRO 1



SPECS

CADRU	
MARIMI	XS, S, M, M/L, L, XL
CULORI	White/Iris
CADRU	Advanced-grade Composite, 12x142mm thru-axle, disc
FURCA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SOC	N/A
COMPONENTE	
GHIDON	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPS	Stratus Lite 3.0
PIPA	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
TIJA SA	Giant D-Fuse SL, composite, -5/+15mm offset
SA	Giant Fleet SL
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM Rival AXS E1
SCHIMBATOR FATA	SRAM Rival AXS E1
SCHIMBATOR SPATE	SRAM Rival AXS E1
FRANE	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
MANETE FRANA	SRAM Rival AXS E1 hydraulic
PINIOANE	SRAM Rival, 12-speed, 10x36
LANT	SRAM Rival E1
ANGRENAJ	SRAM Rival E1 DUB, 33/46 with Quark power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	Giant SLR 1 40 Carbon Disc WheelSystem
BUTUCI	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
SPITE	Sapim
ANVELOPE	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
EXTRAS	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRIE

CADRU	XS	S	M	ML	L	XL
Seat Tube Length (mm)	410	445	480	515	535	565
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	530	545	560	575	595
Head Tube Length (mm)	125	135	150	175	195	215
Head Tube Angle	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Wheelbase (mm)	995	994	998	1010	1025	1040
Chain Stay Length (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Stand Over Height (mm)	705	733	762	796	814	841
Handlebar Width (mm)	404	404	424	424	444	444
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	165	165	170	170	172,5	172,5

Toate specificatiile enumerate se pot schimba fara notificare prealabila.