

DEFY ADVANCED PRO 1

GIANT



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, M/L, L, XL
FARBY	White/Iris
RÁM	Advanced-grade Composite, 12x142mm thru-axle, disc
VIDLICA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
TLMIČ	N/A
KOMPONENTY	
RIADIDLÁ	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPY	Stratus Lite 3.0
PREDSTAVEC	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SEDLOVKA	Giant D-Fuse SL, composite, -5/+15mm offset
SEDADLO	Giant Fleet SL
POHON	
RADENIE	SRAM Rival AXS E1
PREŠMYKAČ	SRAM Rival AXS E1
PREHADZOVAČKA	SRAM Rival AXS E1
BRZDY	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BRZDOVÉ PÁKY	SRAM Rival AXS E1 hydraulic
KAZETA	SRAM Rival, 12-speed, 10x36
REŤAZ	SRAM Rival E1
KLUKY	SRAM Rival E1 DUB, 33/46 with Quark power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant SLR 1 40 Carbon Disc WheelSystem
NÁBOJE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
ŠPICE	Sapim
PNEUMATIKY	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
DOPLNKY	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
LIMITY	
MAXIMÁLNA ŠÍRKA PNEUMATÍK	40mm

Cena: 5 199 €

GEOMETRIA

RÁM	XS	S	M	ML	L	XL
Dĺžka sedlovej trubky (mm)	410	445	480	515	535	565
Uhol sedlovej trubky	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Dĺžka hornej rámovej trubky (mm)	515	530	545	560	575	595
Dĺžka hlavovej trubky (mm)	125	135	150	175	195	215
Uhol hlavovej trubky	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Offset vidlice (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Rázvor (mm)	995	994	998	1010	1025	1040
Dĺžka zadnej stavby (mm)	420	420	420	420	420	420
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	75	75	75	70	70	70
Stack - výška riadenia (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Výška rámu od zeme (mm)	705	733	762	796	814	841
Šírka riaditok (mm)	404	404	424	424	444	444
Dĺžka predstavca (mm)	80	90	100	100	110	110
Dĺžka klúk (mm)	165	165	170	170	172,5	172,5

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.