

DEFY ADVANCED PRO 1

GIANT



SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	White/Iris
RAM	Advanced-grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
BAKDÄMPARE	N/A
KOMponenter	
STYRE	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GREPPAR	Stratus Lite 3.0
STAM	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SADELSTOLPE	Giant D-Fuse SL, composite, -5/+15mm offset
SADEL	Giant Fleet SL
DRIVLINJA	
VÄXLAR	SRAM Rival AXS E1
FRAMVÄXEL	SRAM Rival AXS E1
BAKVÄXEL	SRAM Rival AXS E1
BROMSAR	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BROMSSPAKAR	SRAM Rival AXS E1 hydraulic
KASSETT	SRAM Rival, 12-speed, 10x36
KEDJA	SRAM Rival E1
VEVPARTI	SRAM Rival E1 DUB, 33/46 with Quark power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant SLR 1 40 Carbon Disc WheelSystem
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
EKRAR	Sapim
DÄCK	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
EXTRAFUNKTIONER	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
GRÄNSER	
MAX DÄCKAVSTÄND	40mm

Price: 62 990,00 kr

GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	445	480	515	535	565
Vinkel sadelrör	74,0°	73,5°	73,0°	73,0°	73,0°
Topprörets längd (mm)	530	545	560	575	595
Styrhuvud Längd (mm)	135	150	175	195	215
Vinkel styrhuvud	71,8°	72,5°	72,5°	72,5°	72,5°
Gaffelvinkel (mm)	50	50	50	50	50
Spår (mm)	63,4	58,6	58,6	58,6	58,6
Hjulbas (mm)	994	998	1010	1025	1040
Kedjestagslängd (mm)	420	420	420	420	420
Nedre fäste Drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Stå över höjden (mm)	733	762	796	814	841
Styrets bredd (mm)	404	424	424	444	444
Stamlängd (mm)	90	100	100	110	110
Vevlängd (mm)	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.