

DEFY ADVANCED PRO 2 ULTEGRA



SPECS

| FRAME | |
|------------------|---|
| SIZES | XS, S, M, M/L, L, XL |
| COLOURS | Black Chrome / Black |
| FRAME | Advanced-Grade Composite, disc |
| FORK | Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Giant Contact SL D-Fuse XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm |
| GRIPS | Stratus Lite 3.0 |
| STEM | Giant Contact SL XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:110mm |
| SEATPOST | Giant D-Fuse SL, composite, 16mm offset |
| SADDLE | Giant Fleet SL |
| PEDALS | N/A |
| DRIVETRAIN | |
| SHIFTERS | Shimano Ultegra |
| FRONT DERAILLEUR | Shimano Ultegra |
| REAR DERAILLEUR | Shimano GRX RX-810 |
| BRAKES | Shimano Ultegra hydraulic, Shimano rotors [F]160mm, [R]140mm |
| BRAKE LEVERS | Shimano Ultegra |
| CASSETTE | Shimano Ultegra, 11x34 |
| CHAIN | KMC X11SL-1 |
| CRANKSET | Shimano Ultegra, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | SRAM DUB, press fit |

| WHEELS | |
|--------|--|
| RIMS | Giant SLR 2 36 Carbon Disc WheelSystem |
| HUBS | Giant SLR 2 36 Carbon Disc WheelSystem, 12mm thru-axle |
| SPOKES | Giant SLR 2 36 Carbon Disc WheelSystem |
| TIRES | Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding |
| EXTRAS | Computer mount, tubeless prepared, 35mm max tyre size |

Price: \$5,399.00

GEOMETRY

| FRAME | XS | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 410 | 445 | 480 | 515 | 535 | 565 |
| Seat Tube Angle | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 72.5° |
| Top Tube Length (mm) | 515 | 530 | 545 | 560 | 575 | 595 |
| Head Tube Length (mm) | 120 | 140 | 160 | 185 | 205 | 225 |
| Head Tube Angle | 70.5° | 71.8° | 72.5° | 72.5° | 72.5° | 72.5° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | 50 | 50 |
| Trail (mm) | 71.3 | 63.1 | 58.2 | 58.2 | 58.2 | 58 |
| Wheelbase (mm) | 995 | 995 | 998 | 1010 | 1025 | 1040 |
| Chain Stay Length (mm) | 420 | 420 | 420 | 420 | 420 | 420 |
| Bottom Bracket Drop (mm) | 75 | 75 | 75 | 70 | 70 | 70 |
| Stack (mm) | 522 | 546 | 567 | 586 | 605 | 624 |
| Reach (mm) | 370 | 374 | 377 | 381 | 390 | 398 |
| Stand Over Height (mm) | 731 | 760 | 786 | 816 | 835 | 856 |
| Stem Length (mm) | 80 | 90 | 100 | 100 | 110 | 110 |
| Crank Length (mm) | 170 | 170 | 172.5 | 172.5 | 175 | 175 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C | 700C |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.