

DEFY ADVANCED PRO-RED

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Carbon
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SEATPOST	Giant D-Fuse SL, composite, -5/+15mm offset
SADDLE	Giant Fleet SL
DRIVETRAIN	
SHIFTERS	Sram Red AXS Hydraulic, RED-E1
FRONT DERAILLEUR	Sram Red AXS RED-E-E1
REAR DERAILLEUR	Sram Red AXS RED-E-E1
BRAKES	Sram Red AXS Hydraulic, RED-E1, Sram PaceLine X [F]160[R]160
BRAKE LEVERS	Sram Red AXS Hydraulic, RED-E1
CASSETTE	Sram Red XG-1290, 12-speed, 10-36
CHAIN	Sram RED-E1, 12-speed
CRANKSET	Sram RED E1, DUB , 33/46 with Power Meter XS: 165mm, S: 165mm, M: 170mm, M/L: 170, L: 172.5mm, XL: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 0 40 Carbon Disc WheelSystem
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Aero Carbon
TIRES	CADEX Classics, tubeless, 700x32c (33.5mm), folding
EXTRAS	computer mount, fender mount, water bottle cages, tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	410	445	480	515	535	565
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	530	545	560	575	595
Head Tube Length (mm)	125	135	150	175	195	215
Head Tube Angle	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Wheelbase (mm)	995	994	998	1010	1025	1040
Chain Stay Length (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Stand Over Height (mm)	705	733	762	796	814	841
Handlebar Width (mm)	404	404	424	424	444	444
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	165	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.