

# DEFY ADVANCED SL 0

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLOURS</b>	Arctic Light
<b>FRAME</b>	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
<b>FORK</b>	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR D-Fuse XS:38/40cm, S:38/40cm, M:40/42cm, M/L:40/42cm, L:42/44cm, XL:42/44cm
<b>GRIPS</b>	Stratus Lite 3.0
<b>STEM</b>	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
<b>SEATPOST</b>	Giant D-Fuse SLR, composite, -5/+15mm offset
<b>SADDLE</b>	CADEX AMP
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM RED AXS E1
<b>FRONT DERAILLEUR</b>	SRAM RED AXS E1
<b>REAR DERAILLEUR</b>	SRAM RED AXS E1
<b>BRAKES</b>	SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM RED AXS hydraulic
<b>CASSETTE</b>	SRAM RED XG-1290, 12-speed, 10-36
<b>CHAIN</b>	SRAM RED E1
<b>CRANKSET</b>	SRAM RED E1 DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
<b>BOTTOM BRACKET</b>	SRAM DUB ceramic, press fit

WHEELS	
<b>RIMS</b>	CADEX Ultra 40 WheelSystem, [F]40mm, [R]40mm
<b>HUBS</b>	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	CADEX Super Aero Carbon Spoke
<b>TYRES</b>	CADEX Classics, tubeless, 700x32c (33.5mm), folding
<b>EXTRAS</b>	Computer mount, fender mount, water bottle cages, tubeless prepared, 38mm max tyre size
LIMITS	
<b>MAX TYRE CLEARANCE</b>	38mm

**Price: \$13,999.00**

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	410	445	480	515	535	565
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	515	530	545	560	575	595
Head Tube Length (mm)	125	135	150	175	195	215
Head Tube Angle	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6	58.6	58.6
Wheelbase (mm)	995	994	998	1010	1025	1040
Chain Stay Length (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Stand Over Height (mm)	705	733	762	796	814	841
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	165	165	170	170	172.5	172.5

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.