

DEFY ADVANCED SL 0*

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Arctic Light
FRAME	Advanced SL-Grade Composite, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR D-Fuse XS:38/40cm, S:38/40cm, M:40/42cm, M/L:40/42cm, L:42/44cm, XL:42/44cm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset
SADDLE	CADEX AMP
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM RED AXS HRD, ED-RED-E1
FRONT DERAILLEUR	SRAM RED AXS, FD-RED-E-E1
REAR DERAILLEUR	SRAM RED AXS, RD-RED-E-E1
BRAKES	SRAM RED AXS HRD, ED-RED-E1, SRAM PaceLine X rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM RED AXS HRD, ED-RED-E1
CASSETTE	SRAM RED XG-1290, 12-speed, 10-36
CHAIN	SRAM RED E1, 12-speed
CRANKSET	SRAM RED E1, DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB Ceramic, Press Fit

WHEELS	
RIMS	CADEX Ultra 40 WheelSystem, [F]40mm, [R]40mm
HUBS	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C48 Aero Low Friction Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	CADEX Super Aero Carbon Spoke
TIRES	CADEX Classics, tubeless, 700x32c (33.5mm), folding
EXTRAS	Computer mount, water bottle cages, tubeless prepared, 38mm max tyre size
LIMITS	
MAX TIRE CLEARANCE	38 mm

Price: \$15,999.00

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	410	445	480	515	535	565
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	515	530	545	560	575	595
Head Tube Length (mm)	125	135	150	175	195	215
Head Tube Angle	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6	58.6	58.6
Wheelbase (mm)	995	994	998	1010	1025	1040
Chain Stay Length (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Stand Over Height (mm)	705	733	762	796	814	841
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	165	165	170	170	172.5	172.5

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.