

# DEFY ADVANCED SL 0

GIANT



## TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, M/L, L, XL
VÄRIT	Arctic Light/Chrome
RUNKO	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
HAARUKKA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTIT	
OHJAUSTANKO	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPIT	Stratus Lite 3.0
OHJAINKANNATIN	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SATULATOLPPA	Giant D-Fuse SLR, composite, -5/+15mm offset
SATULA	CADEX AMP
VOIMANSIIRTO	
VAIHDEVIPU	SRAM RED AXS E1
ETUVAIHTAJA	SRAM RED AXS E1
TAKAVAIHTAJA	SRAM RED AXS E1
JARRUT	SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
JARRUKAHVAT	SRAM RED AXS hydraulic
RATASPAKKA	SRAM RED XG-1290, 12-speed, 10x36
KETJUT	SRAM RED E1
KAMPISARJA	SRAM RED E1 DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KESKIÖ	SRAM DUB ceramic, press fit

RENKAAT	
VANTEET	CADEX Ultra 40 WheelSystem, [F]40mm, [R]40mm
NAVAT	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
PINNAT	CADEX Super Aero Carbon Spoke
RENKAAT	CADEX Classics, tubeless, 700x32c (33.5mm), folding
LISÄTIEDOT	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
RAJOITTEET	
MAX RENGASVARA	40mm

Suositusuhinta: 12 799,00 €

## GEOMETRIA

RUNKO	S	M	ML	L	XL
Satulaputken pituus (mm)	445	480	515	535	565
Satulaputken kulma	74,0°	73,5°	73,0°	73,0°	73,0°
Vaakaputken pituus (mm)	530	545	560	575	595
Emäputken pituus (mm)	135	150	175	195	215
Emäputken kulma	71,8°	72,5°	72,5°	72,5°	72,5°
Haarukan offset (mm)	50	50	50	50	50
Trail-mitta (mm)	63,4	58,6	58,6	58,6	58,6
Akseliväli (mm)	994	998	1010	1025	1040
Takahaarukan alaputken pituus (mm)	420	420	420	420	420
Keskiön pudotus (mm)	75	75	70	70	70
Stack-mitta (mm)	541	558	577	596	615
Reach-mitta (mm)	375	380	384	393	402
Standover-mitta (mm)	733	762	796	814	841
Ohjaustangon leveys (mm)	404	424	424	444	444
Ohjainkannattimen pituus (mm)	90	100	100	110	110
Kammen pituus (mm)	165	170	170	172,5	172,5

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.