



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Blue Dragonfly/Black/Chrome
OKVIR	Advanced SL-grade composite, disc
VILICE	Advanced SL-grade composite, full-composite OverDrive Aero steerer, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact SLR D-Fuse XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
OPORA SEDEŽA	Giant SLR D-Fuse, composite, -5/+15mm offset
SEDEŽ	Giant Fleet SLR
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM RED eTap AXS
PREDNJI MENJALNIK	SRAM RED eTap AXS
ZADNJI MENJALNIK	SRAM RED eTap AXS
ZAVORE	SRAM RED eTap AXS hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	SRAM RED eTap AXS hydraulic
VERIŽNIK	SRAM Force, 12-speed, 10x36
VERIGA	SRAM RED D1
GONILKE Z VERIŽNIKI	SRAM RED D1 DUB, 33/46 with Quarq DZero power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	CADEX 36 Disc WheelSystem, [F]36mm, [R]36mm
PESTA	[F] CADEX R1 Hub, CenterLock, 12mm thru-axle [R] CADEX R1-C30 Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
NAPERE	CADEX Aero Carbon Spoke
PLAŠČI	CADEX Classic, tubeless, 700x32c (33.5mm), folding
DODATKI	computer mount, fender mount, water bottle cages, tubeless prepared, 38mm max tire size

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	410	445	480	515	535	565
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	530	545	560	575	595
Višina glave okvirja (mm)	125	135	150	175	195	215
Krmilni kot	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Zamik vpetja osi (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Medosna razdalja (mm)	995	994	998	1010	1025	1040
Dolžina cevi ob verigi (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	527	541	558	577	596	615
Doseg (mm)	369	375	380	384	393	402
Višina zgornje cevi (mm)	705	733	762	796	814	841
Širina krmila (mm)	400	400	420	420	440	440
Dolžina opore krmila (mm)	80	90	100	100	110	110
Dolžina gonilke (mm)	170	170	172,5	172,5	175	175
Velikost obročnikov	700C	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.