

# DEFY ADVANCED SL 0

GIANT



## SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	Arctic Light/Chrome
RAM	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
GAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GREPPAR	Stratus Lite 3.0
STAM	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SADELSTOLPE	Giant D-Fuse SLR, composite, -5/+15mm offset
SADEL	CADEX AMP
DRIVLINJA	
VÄXLAR	SRAM RED AXS E1
FRAMVÄXEL	SRAM RED AXS E1
BAKVÄXEL	SRAM RED AXS E1
BROMSAR	SRAM RED AXS E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
BROMSSPAKAR	SRAM RED AXS hydraulic
KASSETT	SRAM RED XG-1290, 12-speed, 10x36
KEDJA	SRAM RED E1
VEVPARTI	SRAM RED E1 DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BROMSREGLAGE	SRAM DUB ceramic, press fit

HJUL	
FÄLGAR	CADEX Ultra 40 WheelSystem, [F]40mm, [R]40mm
NAV	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
EKRAR	CADEX Super Aero Carbon Spoke
DÄCK	CADEX Classics, tubeless, 700x32c (33.5mm), folding
EXTRAFUNKTIONER	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
GRÄNSER	
MAX DÄCKAVSTÅND	40mm

Price: 144 990,00 kr

## GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	445	480	515	535	565
Vinkel sadelrör	74,0°	73,5°	73,0°	73,0°	73,0°
Topprörets längd (mm)	530	545	560	575	595
Styrhuvud Längd (mm)	135	150	175	195	215
Vinkel styrhuvud	71,8°	72,5°	72,5°	72,5°	72,5°
Gaffelvinkel (mm)	50	50	50	50	50
Spår (mm)	63,4	58,6	58,6	58,6	58,6
Hjulbas (mm)	994	998	1010	1025	1040
Kedjestagslängd (mm)	420	420	420	420	420
Nedre fäste Drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Stå över höjden (mm)	733	762	796	814	841
Styrets bredd (mm)	404	424	424	444	444
Stamlängd (mm)	90	100	100	110	110
Vevlängd (mm)	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.