

DEFY ADVANCED SL 1

GIANT

SPECS

| ΣΚΕΛΕΤΟΣ | |
|----------------------|---|
| ΜΕΓΕΘΗ | XS, S, M, M/L, L, XL |
| ΧΡΩΜΑΤΑ | Dark Green |
| ΣΚΕΛΕΤΟΣ | Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc |
| ΠΙΡΟΥΝΙ | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| ΑΝΑΡΤΗΣΗ | N/A |
| ΕΞΑΡΤΗΜΑΤΑ | |
| ΤΙΜΟΝΙ | Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm |
| GRIPS | Stratus Lite 3.0 |
| ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ | Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm |
| ΛΑΙΜΟΣ Σ'ΕΛΛΑΣ | Giant D-Fuse SLR, composite, -5/+15mm offset |
| Σ'ΕΛΛΑ | Giant Fleet SLR |
| ΠΕΝΤΑΛ | platform pedal [GCS,GTS], N/A [all other GSC] |
| ΜΕΤΑΔΟΣΗ | |
| ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ | SRAM Force AXS E1 |
| ΝΤΕΡΑΓΓΙΕΡ ΕΜΠΡΟΣΘΙΟ | SRAM Force AXS E1 |
| ΝΤΕΡΑΓΓΙΕΡ ΟΠΙΣΘΙΟ. | SRAM Force AXS E1 |
| ΦΡΕΝΑ | SRAM Force E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm |
| ΜΑΝΥΕΤΤΕΣ ΦΡΕΝΩΝ | SRAM Force AXS E1 |
| CASETTE Ή ΕΛΕΥΘΕΡΟ | SRAM Force E1, 12-speed, 10x36 |
| ΑΛΥΣΙΔΑ | SRAM Force E1 |
| ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ | SRAM Force E1 DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm |
| BOTTOM BRACKET | SRAM, press fit |

| WHEELS | |
|--------------------|---|
| ΣΤΕΦΑΝΙΑ | Giant SLR 0 40 Carbon Disc WheelSystem |
| ΚΕΝΤΡΑ | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle |
| ΑΚΤΙΝΕΣ | Sapim |
| ΕΛΑΣΤΙΚΑ | CADEX Classics, tubeless, 700x32c (33.5mm), folding |
| EXTRAS | computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size |
| LIMITS | |
| MAX TIRE CLEARANCE | 40mm |

ΓΕΩΜΕΤΡΙΑ

| ΣΚΕΛΕΤΟΣ | XS | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 410 | 445 | 480 | 515 | 535 | 565 |
| Seat Tube Angle | 74,5° | 74,0° | 73,5° | 73,0° | 73,0° | 73,0° |
| Top Tube Length (mm) | 515 | 530 | 545 | 560 | 575 | 595 |
| Head Tube Length (mm) | 125 | 135 | 150 | 175 | 195 | 215 |
| Head Tube Angle | 70,5° | 71,8° | 72,5° | 72,5° | 72,5° | 72,5° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | 50 | 50 |
| Trail (mm) | 71,6 | 63,4 | 58,6 | 58,6 | 58,6 | 58,6 |
| Wheelbase (mm) | 995 | 994 | 998 | 1010 | 1025 | 1040 |
| Chain Stay Length (mm) | 420 | 420 | 420 | 420 | 420 | 420 |
| Bottom Bracket Drop (mm) | 75 | 75 | 75 | 70 | 70 | 70 |
| Stack (mm) | 527 | 541 | 558 | 577 | 596 | 615 |
| Reach (mm) | 369 | 375 | 380 | 384 | 393 | 402 |
| Stand Over Height (mm) | 705 | 733 | 762 | 796 | 814 | 841 |
| Handlebar Width (mm) | 404 | 404 | 424 | 424 | 444 | 444 |
| Stem Length (mm) | 80 | 90 | 100 | 100 | 110 | 110 |
| Crank Length (mm) | 165 | 165 | 170 | 170 | 172,5 | 172,5 |

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση