

DEFY ADVANCED SL 1

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Dark Green
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPS	Stratus Lite 3.0
STEM	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset
SADDLE	Giant Fleet SLR
PEDALS	platform pedal [GCS,GTS], N/A [all other GSC]
DRIVETRAIN	
SHIFTERS	SRAM Force AXS E1
FRONT DERAILLEUR	SRAM Force AXS E1
REAR DERAILLEUR	SRAM Force AXS E1
BRAKES	SRAM Force E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Force AXS E1
CASSETTE	SRAM Force E1, 12-speed, 10x36
CHAIN	SRAM Force E1
CRANKSET	SRAM Force E1 DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM, press fit

WHEELS	
RIMS	Giant SLR 0 40 Carbon Disc WheelSystem
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim
TYRES	CADEX Classics, tubeless, 700x32c (33.5mm), folding
EXTRAS	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

Price: €8,649.00

GEOMETRY

FRAME	S	M	ML	L
Seat Tube Length (mm)	445	480	515	535
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	530	545	560	575
Head Tube Length (mm)	135	150	175	195
Head Tube Angle	71.8°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50
Trail (mm)	63.4	58.6	58.6	58.6
Wheelbase (mm)	994	998	1010	1025
Chain Stay Length (mm)	420	420	420	420
Bottom Bracket Drop (mm)	75	75	70	70
Stack (mm)	541	558	577	596
Reach (mm)	375	380	384	393
Stand Over Height (mm)	733	762	796	814
Handlebar Width (mm)	404	424	424	444
Stem Length (mm)	90	100	100	110
Crank Length (mm)	165	170	170	172.5

All specifications listed are subject to change without notice.