

# DEFY ADVANCED SL 1



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLORS</b>	Dark Green
<b>FRAME</b>	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
<b>FORK</b>	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
<b>GRIPS</b>	Stratus Lite 3.0
<b>STEM</b>	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
<b>SEATPOST</b>	Giant D-Fuse SLR, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Fleet SLR
<b>PEDALS</b>	platform pedal [GCS,GTS], N/A [all other GSC]
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Force AXS E1
<b>FRONT DERAILLEUR</b>	SRAM Force AXS E1
<b>REAR DERAILLEUR</b>	SRAM Force AXS E1
<b>BRAKES</b>	SRAM Force E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Force AXS E1
<b>CASSETTE</b>	SRAM Force E1, 12-speed, 10x36
<b>CHAIN</b>	SRAM Force E1
<b>CRANKSET</b>	SRAM Force E1 DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
<b>BOTTOM BRACKET</b>	SRAM, press fit

WHEELS	
<b>RIMS</b>	Giant SLR 0 40 Carbon Disc WheelSystem
<b>HUBS</b>	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim
<b>TIRES</b>	CADEX Classics, tubeless, 700x32c (33.5mm), folding
<b>EXTRAS</b>	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	40mm

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	410	445	480	515	535	565
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	530	545	560	575	595
Head Tube Length (mm)	125	135	150	175	195	215
Head Tube Angle	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Wheelbase (mm)	995	994	998	1010	1025	1040
Chain Stay Length (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Stand Over Height (mm)	705	733	762	796	814	841
Handlebar Width (mm)	404	404	424	424	444	444
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	165	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.