



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Dark Green
OKVIR	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VILICE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact SLR D-Fuse XS:404/380mm, S:404/380mm, M:424/400mm, M/L:424/400mm, L:444/420mm, XL:444/420mm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
OPORA SEDEŽA	Giant D-Fuse SLR, composite, -5/+15mm offset
SEDEŽ	Giant Fleet SLR
PEDALA	platform pedal [GCS,GTS], N/A [all other GSC]
POGON	
PRESTAVNE ROČICE	SRAM Force AXS E1
PREDNJI MENJALNIK	SRAM Force AXS E1
ZADNJI MENJALNIK	SRAM Force AXS E1
ZAVORE	SRAM Force E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	SRAM Force AXS E1
VERIŽNIK	SRAM Force E1, 12-speed, 10x36
VERIGA	SRAM Force E1
GONILKE Z VERIŽNIKI	SRAM Force E1 DUB, 33/46 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM, press fit

OBROČNIKI	
OBROČI	Giant SLR 0 40 Carbon Disc WheelSystem
PESTA	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	CADEX Classics, tubeless, 700x32c (33.5mm), folding
DODATKI	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	410	445	480	515	535	565
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	530	545	560	575	595
Višina glave okvirja (mm)	125	135	150	175	195	215
Krmilni kot	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Zamik vpetja osi (mm)	50	50	50	50	50	50
Trail (mm)	71,6	63,4	58,6	58,6	58,6	58,6
Medosna razdalja (mm)	995	994	998	1010	1025	1040
Dolžina cevi ob verigi (mm)	420	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	527	541	558	577	596	615
Doseg (mm)	369	375	380	384	393	402
Višina zgornje cevi (mm)	705	733	762	796	814	841
Širina krmila (mm)	404	404	424	424	444	444
Dolžina opore krmila (mm)	80	90	100	100	110	110
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.