

DEFY ADVANCED SL 1

GIANT



SPECIFIKACIJE

OKVIR	
OKVIR	Advanced SL-Grade Composite, 12x142mm thru-axle, Integrated Seatpost, Disc
VILICE	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
KOMPONENTE	
KRMILO	Contact SLR D-Fuse
GRIPS	Stratus Lite 3.0 w/ gel back
OPORA KRMILA	Giant Contact SLR Aerolight, -10 degree
OPORA SEDEŽA	Giant D-Fuse SLR w/ offset -5/+15
SEDEŽ	Giant Fleet SLR 9mm Carbon Rail With Giant ParticleFlow technology
PEDALA	GCS,GTS:Platform Pedal Rest GSC : no pedal
HEADSET	HS-GT-01
POGON	
PRESTAVNE ROČICE	SRAM Force AXS E1
PREDNJI MENJALNIK	SRAM Force AXS E1
ZADNJI MENJALNIK	SRAM Force AXS E1, Max 36T
ZAVORE	SRAM Force AXS E1 HRD
ZAVORNE ROČICE	SRAM Force AXS E1 HRD
VERIŽNIK	SRAM Force E1, 12-speed, 10x36 XG-1270-E1
VERIGA	SRAM Force E1, 12-speed
GONILKE Z VERIŽNIKI	SRAM Force E1 DUB,33/46 with power meter
BOTTOM BRACKET	SRAM DUB, Press Fit

OBROČNIKI	
OBROČI	Giant SLR 0 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
PESTA	Giant SLR 0 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
NAPERE	Giant SLR 0 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
PLAŠČI	CADEX Classic Tubeless, 700x32c (33.5mm effective), 170 TPI, Folding
DODATKI	Computer mount, tubeless prepared Bottle Cages
LIMITS	
MAX TIRE CLEARANCE	700x40mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	515	530	545	560	575	595
Višina glave okvirja (mm)	125	135	150	175	195	215
Krmilni kot	70,5°	71,8°	72,5°	72,5°	72,5°	72,5°
Medosna razdalja (mm)	995,2	994,4	997,7	1010	1025,2	1040,4
Dolžina cevi ob verigi (mm)	420	420	420	420	420	420
Oddaljenost zgornje cevi od gonilne osi (mm)	527	541	558	577	596	615
Doseg (mm)	368,9	374,9	379,8	383,7	392,9	402
Višina zgornje cevi (mm)	705	733	762	796	814	841
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.