

DEFY ADVANCED SL FRAMESET

GIANT



SPECS

FRAME	
SIZES	S, M, M/L, L, XL
COLOURS	Raw Carbon/Airglow, Artic Blast/Iris
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset

WHEELS	
EXTRAS	computer mount, fender mount, water bottle cages, tubeless prepared, 40mm max tire size
LIMITS	
MAX TYRE CLEARANCE	40mm

Price: £3,499.00

GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	445	480	515	535	565
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°	73.0°
Top Tube Length (mm)	530	545	560	575	595
Head Tube Length (mm)	135	150	175	195	215
Head Tube Angle	71.8°	72.5°	72.5°	72.5°	72.5°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	63.4	58.6	58.6	58.6	58.6
Wheelbase (mm)	994	998	1010	1025	1040
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Stand Over Height (mm)	733	762	796	814	841
Handlebar Width (mm)	404	424	424	444	444
Stem Length (mm)	90	100	100	110	110
Crank Length (mm)	165	170	170	172.5	172.5

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.