

DEFY ADVANCED SL FRAMESET



SPECS

FRAME	
SIZES	S, M, M/L, L, XL
COLOURS	Gloss Artic Blast/Iris
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
SEATPOST	Giant D-Fuse SLR, composite, -5/+15mm offset
DRIVETRAIN	
SHIFTERS	Compatible with Shimano Di2, SRAM AXS/eTap, new Campagnolo Super Record groupsets. Not compatible with any mechanical groupsets.
BOTTOM BRACKET	Press fit 41x86.5mm. Not included

WHEELS	
EXTRAS	Out front computer mount, fender mount, water bottle cages, headset and spacers, axles
LIMITS	
MAX TIRE CLEARANCE	40mm

Price: €3,999.00

GEOMETRY

FRAME	S	L	XL
Seat Tube Length (mm)	445	535	565
Seat Tube Angle	74.0°	73.0°	73.0°
Top Tube Length (mm)	530	575	595
Head Tube Length (mm)	135	195	215
Head Tube Angle	71.8°	72.5°	72.5°
Fork Rake (mm)	50	50	50
Trail (mm)	63.4	58.6	58.6
Wheelbase (mm)	994	1025	1040
Chain Stay Length (mm)	420	420	420
Bottom Bracket Drop (mm)	75	70	70
Stack (mm)	541	596	615
Reach (mm)	375	393	402
Stand Over Height (mm)	733	814	841
Handlebar Width (mm)	400	440	440
Stem Length (mm)	90	110	110
Crank Length (mm)	170	175	175
Wheel Size	700C	700C	700C

All specifications listed are subject to change without notice.