

DEFY ADVANCED SL FRAMESET



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Arctic Blast/Iris
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VOORVORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ONDERDELEN	
ZADELPEEN	Giant D-Fuse SLR, composite, -5/+15mm offset

WIELSET	
EXTRA'S	computer mount, fender mount, water bottle cages, tubeless prepared, 38mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	40mm

Adviesprijs: € 3.599,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	445	480	515	535	565
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	530	545	560	575	595
Balhoofdbuis Lengte (mm)	135	150	175	195	215
Balhoofdbuis Hoek	71,8°	72,5°	72,5°	72,5°	72,5°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	63,4	58,6	58,6	58,6	58,6
Wielbasis (mm)	994	998	1010	1025	1040
Liggende achtervork lengte (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Stand Over Height (mm)	733	762	796	814	841
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	100	110	110
Cranklengte (mm)	170	172,5	172,5	175	175
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.