

DEFY ADVANCED-UI2

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, M/L, L, XL
FARVER	Tempest Purple
RAMME	Advanced-Grade Composite, 12x142mm thru-axle
FORGAFFEL	Advanced-Grade Composite, Full-Composite OverDrive Steerer, 12x100mm thru-axle
KOMPONENTER	
STYR	Contact SL D-Fuse XS: 410/380, S 410/380, M: 430/400, ML: 430/400, L: 450/420, XL: 450/420
GREB / STYRBÅND	Stratus Lite 3.0
FREMPIND	Giant Contact AeroLight XS: 80, S: 90, M: 100, ML: 100, L: 110, XL: 110
SADELPIND	Giant D-Fuse Composite Offset 14mm
SADEL	Giant Approach
GEARGRUPPE	
SKIFTEGREB	Shimano Ultegra Di2 HRD
FORSKIFTER	Shimano Ultegra Di2
BAGSKIFTER	Shimano Ultegra Di2
BREMSE	Shimano Ultegra Di2 HRD, Shimano RT-CL700, [F]160[R]160
BREMSEGREB	Shimano Ultegra Di2 HRD
KASSETTE	Shimano CS-R8100, 11X34
KÆDE	KMC X12L-1
KRANKSÆT	Shimano Ultegra (R8100), 34/50 XS: 165, S: 165, M: 170, ML: 170, L: 172.5, XL: 172.5
KRANKBOKS	Shimano, PressFit

HJUL	
FÆLGE	Giant SLR 2 40 Carbon Disc Wheel System
NAV	[F] Giant Alloy Hub, CenterLock, 12mm thru-axle, [R] Giant Alloy Hub, 3-pawl driver, CenterLock, 12mm thru-axle
EGER	Sapim
DÆK	Giant Gavia Fondo 0 Tubeless, 700x32c (33.5mm effective), 170 TPI, Folding
EKSTRA	tubeless prepared, 40mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	40mm

Pris: 32.549,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørslængde (mm)	445	480	515	535	565
Sadelrørvinkel	74,0°	73,5°	73,0°	73,0°	73,0°
Overrørslængde (mm)	530	545	560	575	595
Kronrørslængde (mm)	135	150	175	195	215
Kronrørvinkel	71,8°	72,5°	72,5°	72,5°	72,5°
Forgaffel fremspring (rake) (mm)	50	50	50	50	50
Sti (mm)	63,4	58,6	58,6	58,6	58,6
Akselafstand (mm)	994	998	1010	1025	1040
Kædestagslængde (mm)	420	420	420	420	420
Krankboks drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Skridthøjde (mm)	733	762	796	814	841
Styrbredde (mm)	410	430	430	450	450
Frempindslængde (mm)	90	100	100	110	110
Pedalarmslængde (mm)	165	170	170	172,5	172,5

Alle de anførte specifikationer kan ændres uden varsel.