

DEFY ADVANCED-UI2

GIANT



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, ML, L, XL
FARBE	Tempest Purple
RAHMEN	Advanced-Grade Composite, 12x142mm thru-axle
GABEL	Advanced-Grade Composite, Full-Composite OverDrive Steerer, 12x100mm thru-axle
KOMPONENTEN	
LENKER	Contact SL D-Fuse XS: 410/380, S 410/380, M: 430/400, ML: 430/400, L: 450/420, XL: 450/420
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact AeroLight XS: 80, S: 90, M: 100, ML: 100, L: 110, XL: 110
SATTELSTÜTZE	Giant D-Fuse Composite Offset 14mm
SATTEL	Giant Approach
ANTRIEB	
SCHALTHEBEL	Shimano Ultegra Di2 HRD
UMWERFER	Shimano Ultegra Di2
SCHALTWERK	Shimano Ultegra Di2
BREMSEN	Shimano Ultegra Di2 HRD, Shimano RT-CL700, [F]160[R]160
BREMSHEBEL	Shimano Ultegra Di2 HRD
KASSETTE	Shimano CS-R8100, 11X34
KETTE	KMC X12L-1
KURBEL	Shimano Ultegra (R8100), 34/50 XS: 165, S: 165, M: 170, ML: 170, L: 172.5, XL: 172.5
TRETLAGER	Shimano, PressFit

LAUFRÄDER	
FELGEN	Giant SLR 2 40 Carbon Disc Wheel System
NABE	[F] Giant Alloy Hub, CenterLock, 12mm thru-axle, [R] Giant Alloy Hub, 3-pawl driver, CenterLock, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant Gavia Fondo 0 Tubeless, 700x32c (33.5mm effective), 170 TPI, Folding
EXTRAS	tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	410	445	480	515	535	565
Seat Post Insertion Depth (mm)	190	190	190	190	190	190
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	515	530	545	560	575	595
Steuerrohr-Länge (mm)	125	135	150	175	195	215
Steuerrohr-Winkel	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6	58.6	58.6
Radstand (mm)	995	994	998	1010	1025	1040
Kettenstreben-Länge (mm)	420	420	420	420	420	420
Tretlager-Höhe (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Überstandshöhe (mm)	705	733	762	796	814	841
Lenkerbreite (mm)	410	410	430	430	450	450
Vorbaulänge (mm)	80	90	100	100	110	110
Kurbellänge (mm)	165	165	170	170	172.5	172.5

Spezifikations-, Preis- und Farbänderungen vorbehalten.