

DEFY ADVANCED-UI2



SPECS

RAM	
STORLEKAR	S, M, M/L, L, XL
FÄRGER	Tempest Purple
RAM	Advanced-Grade Composite, 12x142mm thru-axle
GAFFEL	Advanced-Grade Composite, Full-Composite OverDrive Steerer, 12x100mm thru-axle
KOMPONENTER	
STYRE	Contact SL D-Fuse XS: 410/380, S 410/380, M: 430/400, ML: 430/400, L: 450/420, XL: 450/420
GREPPAR	Stratus Lite 3.0
STAM	Giant Contact AeroLight XS: 80, S: 90, M: 100, ML: 100, L: 110, XL: 110
SADELSTOLPE	Giant D-Fuse Composite Offset 14mm
SADEL	Giant Approach
DRIVLINAN	
VÄXLAR	Shimano Ultegra Di2 HRD
FRAMVÄXEL	Shimano Ultegra Di2
BAKVÄXEL	Shimano Ultegra Di2
BROMSAR	Shimano Ultegra Di2 HRD, Shimano RT-CL700, [F]160[R]160
BROMSSPAKAR	Shimano Ultegra Di2 HRD
KASSETT	Shimano CS-R8100, 11X34
KEDJA	KMC X12L-1
VEVPARTI	Shimano Ultegra (R8100), 34/50 XS: 165, S: 165, M: 170, ML: 170, L: 172.5, XL: 172.5
BROMSREGLAGE	Shimano, PressFit

HJUL	
FÄLGAR	Giant SLR 2 40 Carbon Disc Wheel System
NAV	[F] Giant Alloy Hub, CenterLock, 12mm thru-axle, [R] Giant Alloy Hub, 3-pawl driver, CenterLock, 12mm thru-axle
EKRAR	Sapim
DÄCK	Giant Gavia Fondo 0 Tubeless, 700x32c (33.5mm effective), 170 TPI, Folding
EXTRAFUNKTIONER	tubeless prepared, 40mm max tire size
GRÄNSER	
MAX DÄCKAVSTÅND	40mm

Price: 48 000,00 kr

GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	445	480	515	535	565
Seat Post Insertion Depth (mm)	190	190	190	190	190
Vinkel sadelrör	74,0°	73,5°	73,0°	73,0°	73,0°
Topprörets längd (mm)	530	545	560	575	595
Styrhuvud Längd (mm)	135	150	175	195	215
Vinkel styrhuvud	71,8°	72,5°	72,5°	72,5°	72,5°
Gaffelvinkel (mm)	50	50	50	50	50
Spår (mm)	63,4	58,6	58,6	58,6	58,6
Hjulbas (mm)	994	998	1010	1025	1040
Kedjestagslängd (mm)	420	420	420	420	420
Nedre fäste Drop (mm)	75	75	70	70	70
Stack (mm)	541	558	577	596	615
Reach (mm)	375	380	384	393	402
Stå över höjden (mm)	733	762	796	814	841
Styrets bredd (mm)	410	430	430	450	450
Stamlängd (mm)	90	100	100	110	110
Vevlängd (mm)	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.