

ENTOUR E+ 0 DAMES



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Core, 50Nm, Powered by Yamaha
BEDIENINGSUNIT	RideControl Ergo 2
DISPLAY	RideDash EVO
ACCU	Persoonlijke accukeuze: 400Wh, of 500Wh (adviesprijs op basis van 400Wh)
FRAME	
MATEN	S, M, L
KLEUREN	Gunmetal Black, Grey Dawn, Cold Night, Charcoal Plum, Almond
FRAME	ALUXX aluminium, monotube extra low-stepthrough design.
VOORVORK	SR Suntour NEX 50mm Suspension
ONDERDELEN	
STUUR	Aluminium 30degree sweep
STUURPEN	Aluminum angle adjustable 1¼"x 90mm
ZADEL	Selle Royal Essenza Plus
PEDALEN	Anti-slip
AFMONTAGE	
SHIFTERS	Shimano 8sp RevoShift
REMMEN	Shimano BR-MT200 hydraulic disc
REMHENDELS	Shimano BL-MT200
CASSETTE	18T
AANDRIJVING	KMC Z1e HX, e-bike optimized
CRANKSET	Giant aluminium

WIELSET	
VELGEN	Giant Double Wall Aluminum 622x19
NAVEN	Shimano HB-TX505 [F], Shimano Nexus 8 disc brake [R]
SPAKEN	Sapim Leader, stainless 14G(2.0mm) [F]Sapim Strong, stainless 13-14G(2.3-2.0mm) butted [R]
BANDEN	Banden met anti-leklaag
ACCESSOIRES	
VERLICHTING	Axa Blueline 30 LED [F]Spanninga Solo LED [R]
DRAGER	Custom design for rear battery with MIK system

Adviesprijs: € 2.499,00

GEOMETRIE

FRAME	S	M	L
Zitbuis Lengte (mm)	450	500	550
Zitbuis Hoek	72,0°	72,0°	72,0°
Frame Lengte (horizontaal) (mm)	580	590	610
Balhoofdbuis Lengte (mm)	160	160	180
Balhoofdbuis Hoek	70,0°	70,0°	70,0°
Vork Sprong (mm)	43	43	43
Naloop (mm)	82	82	82
Wielbasis (mm)	1095	1105	1125
Liggende achtervork lengte (mm)	470	470	470
Bottom Bracket Drop (mm)	60	60	60
Stack (mm)	630	630	649
Reach (mm)	375	385	399
Stuur breedte (mm)	670	670	670
Stuurpen Lengte (mm)	90	90	90
Cranklengte (mm)	170	170	170
Wielmaat	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.