

EXPLORE E+ 0 HEREN

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	85Nm
BEDIENINGSUNIT	Giant RideControl Go 2 Giant RideControl Ergo4 Dual Remotes
DISPLAY	Giant RideDash EVO 2.0, high-angle visibility, 3" full color LCD display, on-board navigation
ACCU	CO2 Neutral production Giant EnergyPak 800Wh, with Plus 250Wh range extender compatible
LADER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	M, L, XL, XXL
KLEUREN	Snow Drift
FRAME	Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VOORVORK	SR Suntour XCR34 2CR air boost 100mm travel 15x110mm AH axle
DEMPER	n/a
ONDERDELEN	
STUUR	Giant Contour Comfort Riser 31.8x720mm
HANDVATTEN	RideControl Ergo4 Integrated Trekking (w/Bar-end)
STUURPEN	Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm)
ZADELPEN	Giant Contact Switch Dropper Seatpost (100mm Travel)
ZADEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALEN	VPE-537 PP Platform Pedal
AFMONTAGE	
SHIFTERS	Enviolo Trekking Automatiq Integrated
ACHTERDERAILLEUR	Enviolo Trekking Automatiq Modular 40T Spline
REMMEN	Shimano Deore XT, BR-M8120, hydraulic disc, 4-piston, 203mm [F] 180mm [R]
REMHENDELS	Shimano Deore XT
CASSETTE	Gates CDX stainless steel 22T rear sprocket
AANDRIJVING	Gates CDX Carbon Drive 120T CenterTrack belt
CRANKSET	Forged alloy spider w/chainguard BCD 104, Gates CDX front sprocket 46T Forged aluminum crank arms

WIELSET	
VELGEN	Giant eX25, Tubeless Ready, 622x25 Aluminium
NAVEN	Giant eTracker Boost 6-bolt disc 15x110mm [F] Enviolo Trekking Automatiq Modular 40T spline 6-bolt disc 148mm [R]
SPAKEN	Stainless steel, e-bike optimized
BANDEN	Crosscut Gravel 1, 700x57c, Foldable, Tubeless Ready, w/ Reflection Strip
EXTRA'S	Aegis Tire Checker
ACCESSOIRES	
VERLICHTING	Supernova Mini 3 [F] Rear Rack Integrated tail light [R]
SLOT	ABUS Xplus battery lock
DRAGER	MIK rack. System bag & basket compatible Tail light integrated Aegis Radar spec-in
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

Adviesprijs: € 5.899,00

GEOMETRIE

FRAME	M	L	XL	XXL
Zitbuis lengte (mm)	435	485	535	585
Zitbuis hoek	73,0°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	600	610	630	650
Balhoofdbuis Lengte (mm)	140	155	170	185
Balhoofdbuis Hoek	69,5°	69,5°	69,5°	69,5°
Vork Sprong (mm)	51	51	51	51
Wielbasis (mm)	1144	1155	1176	1197
Liggende achtervork lengte (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	668	682	696	710
Reach (mm)	396	401	417	433
Stuur breedte (mm)	690	760	760	760
Stuurpen Lengte (mm)	80	100	100	100
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.