

EXPLORE E+ 1 625 DASH STAGGER

GIANT



SPECIFICATIES

| HYBRID CYCLING TECHNOLOGY | |
|---------------------------|--|
| MOTOR | SyncDrive Sport, 70Nm, powered by Yamaha |
| BEDIENINGSUNIT | Giant RideControl Dash |
| DISPLAY | Giant RideControl Dash |
| ACCU | Giant EnergyPak Smart Integrated 625 |
| FRAME | |
| MATEN | S, M, L, XL |
| KLEUREN | Gunmetal Black |
| FRAME | ALUXX SL aluminum, Overdrive 1½ - 1¾" head tube, integrated KS18 kickstand mount |
| VOORVORK | SR Suntour NEX E25 NLO 63mm travel 15AH |
| ONDERDELEN | |
| STUUR | Giant Connect XC Riser 31.8x690mm |
| STUURPEN | Giant Contact |
| ZADEL | Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium |
| ZADEL | Selle Royal Vivo Ergo Moderate |
| PEDALEN | Aluminum Platform |
| AFMONTAGE | |
| SHIFTERS | Shimano Deore |
| VOORDERAILLEUR | Shimano Deore |
| ACHTERDERAILLEUR | Shimano Deore, 10-Speed, Shadow+ |
| REMMEN | Shimano BR-MT200, hydraulic disc, 180mm |
| REMHENDELS | Shimano BL-MT200 |
| CASSETTE | Shimano CS-M4100, 11-42T, 10-Speed |
| AANDRIJVING | KMC e.10 Sport, e-bike optimized |
| CRANKSET | Forged Alloy minimal Q-factor, 36/48T |

| WIELSET | |
|-------------|---|
| VELGEN | Giant eX 2, Tubeless Ready, 700c Aluminium |
| NAVEN | Giant eTracker, [F] 15mm Axle [R] 135mm QR |
| SPAKEN | Stainless steel |
| BANDEN | Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready, Reflex |
| EXTRA'S | Giant EnergyPak 6A Smart Charger |
| ACCESSOIRES | |
| VERLICHTING | Axa BlueLine 50Lux Steady E6 frontAxa BlueLine Steady E6 rear |
| DRAGER | MIK rack. System bag & basket compatible |

Adviesprijs: € 3.499,00

GEOMETRIE

| FRAME | S | M | L |
|---------------------------------|-------|-------|-------|
| Zitbuis lengte (mm) | 435 | 485 | 535 |
| Zitbuis hoek | 73,0° | 73,0° | 73,0° |
| Frame Lengte (horizontaal) (mm) | 570 | 590 | 610 |
| Balhoofdbuis Lengte (mm) | 130 | 140 | 155 |
| Balhoofdbuis Hoek | 69,5° | 69,5° | 69,5° |
| Vork Sprong (mm) | 42 | 42 | 42 |
| Naloop (mm) | 91,3 | 91,3 | 91,3 |
| Wielbasis (mm) | 1112 | 1121 | 1142 |
| Liggende achtervork lengte (mm) | 455 | 455 | 455 |
| Bottom Bracket Drop (mm) | 60 | 60 | 60 |
| Stack (mm) | 609 | 618 | 633 |
| Reach (mm) | 383 | 401 | 416 |
| Stand Over Height (mm) | 682 | 676 | 665 |
| Stuur breedte (mm) | 690 | 690 | 690 |
| Stuurpen Lengte (mm) | 60 | 70 | 80 |
| Cranklengte (mm) | 170 | 170 | 170 |
| Wielmaat | 700C | 700C | 700C |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.