

EXPLORE E+ 1 DOUBLE DIAMOND

GIANT



SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
MOTOR	Giant SyncDrive Pro2, 85Nm PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Go 2 Giant RideControl Ergo4 Dual Remotes
ECRÃ	Giant RideDash EVO 2.0, high-angle visibility, 3" full color LCD display, on-board navigation
BATERIA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604)
AUTONOMIA	CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CARREGADOR	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
QUADRO	
TAMANHOS	M, L, XL, XXL
CORES	Metallic Navy
QUADRO	Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
FORQUILHA	SR Suntour XCR34 2CR air boost 100mm travel 15x110mm AH axle
AMORTECEDORES	n/a
COMPONENTES	
GUIADOR	Giant Contour Comfort Riser 31.8x720mm
PUNHOS	RideControl Ergo4 Integrated Trekking (w/Bar-end)
AVANÇO	Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm)
ESPIÃO DE SELIM	Giant Contact Switch Dropper Seatpost (100mm Travel)
SELIM	Selle Royal Vivo Ergo Moderate Unisex
PEDAIS	VPE-537 PP Platform Pedal
TRANSMISSÃO	
MANETES	Shimano Cues Di2 E-Shift
DESVIADOR TRASEIRO	Shimano Cues Di2, 11-Speed
TRAVÕES	Shimano Deore, BR-MT420, hydraulic disc, 4-piston, 203mm [F] 180mm [R]
MANÍPULOS DOS TRAVÕES	Shimano BL-M401
CASSETTE	Shimano, 11-45T, 11-speed
CORRENTE	Shimano Linkglide CN-LG500
CONJUNTO PEDALEIRO	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 42T

RODAS	
AROS	Giant eX25, Tubeless Ready, 622x25 Aluminium
CUBOS	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
RAIOS	Stainless steel, e-bike optimized
PNEUS	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
EXTRAS	Aegis Tire Checker
ACESSÓRIOS	
LUZES	Supernova Mini 3 [F] Rear Rack Integrated tail light [R]
CADEADO	ABUS Xplus battery lock
PORTA-BICICLETAS	MIK rack. System bag & basket compatible Tail light integrated Aegis Radar compatible
GUARDA LAMAS/PROTECTOR DE CORRENTE	Alluminum
LIMITES	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

Preço: 4 049,00 €

GEOMETRIA

QUADRO	M	L	XL
Comprimento do tubo do assento (mm)	435	485	535
Ângulo do tubo do assento	73,0°	73,0°	73,0°
Comprimento do tubo superior (mm)	600	610	630
Comprimento do tubo principal (mm)	140	155	170
Ângulo do tubo principal	69,5°	69,5°	69,5°
Garfo ancinho (mm)	51	51	51
distância entre eixos (mm)	1144	1155	1176
Comprimento Chain Stay (mm)	470	470	470
Suporte inferior (mm)	60	60	60
Pilha (mm)	668	682	696
Alcançar (mm)	396	401	417
Largura do guidão (mm)	690	760	760
Comprimento da haste (mm)	80	100	100
Tamanho da roda	29"	29"	29"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.