



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	SyncDrive Sport 2, 75Nm, powered by Yamaha
SENSOR	Giant RideControl Dash, Smart Assist automatic mode, 5 support levels, USB-C (10W)
PRIKAZ	RideControl Dash, full color lcd screen
BATERIJA	EnergyPak Smart 625, EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIČINE	M, L, XL, XXL
BOJE	Misty Forest , Cordovan
OKVIR	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VILICA	SR Suntour XCM34 LO, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
AMORTIZER	n/a
KOMPONENTE	
VOLAN	Giant Connect Riser 31.8x690mm
GRIPS	Giant Connect Ergo Max w/bar-end
LULA VOLANA	Giant Contact (S/M: 80mm L/XL/XXL 100mm)
CIJEV SJEDALA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SJEDALO	Selle Royal Vivo Ergo Moderate Unisex
PEDALE	Aluminum Platform
POGON	
RUČICE MJENJAČA	Shimano Deore, LinkGlide
PREDNJI MJENJAČ	n/a
STRAŽNJI MJENJAČ	Shimano Deore LinkGlide, 10-speed, Shadow+
KOČNICE	Shimano BR-MT200, hydraulic disc, 180mm
RUČICE KOČNICA	Shimano BL-MT201
KAZETA	Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed
LANAC	Shimano LinkGlide, CN-LG500
POGON	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
OSOVINA POGONA (BB)	n/a

KOTAČI	
OBRUČI	eX25, Tubeless Ready, 622x25 Aluminium
NABE	Giant eTracker, [F] 110x15 [R] 142x12
ŽBICE	Stainless steel, e-bike optimized
GUME	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready
DODACI	KSA40 direct mount kickstand
DODACI	
SVJETLA	Recon E HL50 StVZO [F]AXA NYX 6-12V E-bike tail light with brake sensor [R]
LOKOTI	ABUS Xplus battery lock
NOSAČ	MIK rack. System bag & basket compatible
BLATOBRA NI / ŠTITNIK LANCA	Aluminum Fenders

GEOMETRIJA

OKVIR	M	L	XL	XXL
Dužina cijevi sjedala (mm)	435	485	535	585
Kut cijevi sjedala	73,0°	73,0°	73,0°	73,0°
Dužina gornje cijevi (mm)	600	610	630	650
Dužina prednje cijevi (mm)	140	155	170	185
Kut vilice	69,5°	69,5°	69,5°	69,5°
Zakrivljenost vilice (offset) (mm)	51	51	51	51
Staza (mm)	84	84	84	84
Međuosovinski razmak kotača (mm)	1144	1155	1176	1197
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	470	470	470	470
Položaj osovine pogona (mm)	60	60	60	60
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	668	682	696	710
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	396	401	417	433
Prekoračna visina (mm)	759	793	824	856
Širina volana (mm)	690	690	690	690
Dužina lule volana (mm)	80	100	100	100
Dužina poluge pedale (mm)	170	170	170	170
Veličina kotača	29"	29"	29"	29"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.