

# EXPLORE E+ 1 GTS

**GIANT**

## SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDrive Sport 2, 75Nm, powered by Yamaha
TIPALO	Giant RideControl Dash, Smart Assist automatic mode, 5 support levels, USB-C (10W)
PRIKAZOVALNIK	RideControl Dash, full color lcd screen
BATERIJA	EnergyPak Smart 625, EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	M, L, XL, XXL
BARVE	Misty Forest , Cordovan
OKVIR	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VILICE	SR Suntour XCM34 LO, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
AMORTIZER	n/a
KOMPONENTE	
KRMILO	Giant Connect Riser 31.8x690mm
GRIPS	Giant Connect Ergo Max w/bar-end
OPORA KRMILA	Giant Contact (S/M: 80mm L/XL/XXL 100mm)
OPORA SEDEŽA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDEŽ	Selle Royal Vivo Ergo Moderate Unisex
PEDALA	Aluminum Platform
POGON	
PRESTAVNE ROČICE	Shimano Deore, LinkGlide
PREDNJI MENJALNIK	n/a
ZADNJI MENJALNIK	Shimano Deore LinkGlide, 10-speed, Shadow+
ZAVORE	Shimano BR-MT200, hydraulic disc, 180mm
ZAVORNE ROČICE	Shimano BL-MT201
VERIŽNIK	Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed
VERIGA	Shimano LinkGlide, CN-LG500
GONILKE Z VERIŽNIKI	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
BOTTOM BRACKET	n/a

OBROČNIKI	
OBROČI	eX25, Tubeless Ready, 622x25 Aluminium
PESTA	Giant eTracker, [F] 110x15 [R] 142x12
NAPERE	Stainless steel, e-bike optimized
PLAŠČI	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready
DODATKI	KSA40 direct mount kickstand
DODATNA OPREMA	
SVETILA	Recon E HL50 StVZO [F]JAXA NYX 6-12V E-bike tail light with brake sensor [R]
KLJUČAVNICA	ABUS Xplus battery lock
PRTLJAŽNIK	MIK rack. System bag & basket compatible
BLATNIKI/ŠČITNIK VERIGE	Aluminum Fenders

## GEOMETRIJA

OKVIR	M	L	XL	XXL
Dolžina sedežne cevi (mm)	435	485	535	585
Kot sedežne cevi	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	600	610	630	650
Višina glave okvirja (mm)	140	155	170	185
Krmlni kot	69,5°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	51	51	51	51
Trail (mm)	84	84	84	84
Medosna razdalja (mm)	1144	1155	1176	1197
Dolžina cevi ob verigi (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	668	682	696	710
Doseg (mm)	396	401	417	433
Višina zgornje cevi (mm)	759	793	824	856
Širina krmila (mm)	690	690	690	690
Dolžina opore krmila (mm)	80	100	100	100
Dolžina gonilke (mm)	170	170	170	170
Velikost obročnikov	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.