

EXPLORE E+ 1 HEREN

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY

MOTOR	SyncDrive Sport 2, 75Nm, powered by Yamaha
BEDIENINGSUNIT	Giant RideControl Dash, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	RideControl Dash, full color lcd screen
ACCU	EnergyPak Smart 625, EnergyPak Plus 250 range extender compatible
LADER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile

FRAME

MATEN	M, L, XL, XXL
KLEUREN	Misty Forest
FRAME	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VOORVORK	SR Suntour XCM34 LO, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
DEMPER	n/a

ONDERDELEN

STUUR	Giant Connect Riser 31.8x690mm
HANDVATTEN	Giant Connect Ergo Max w/bar-end
STUURPEN	Giant Contact (S/M: 80mm L/XL/XXL 100mm)
ZADELPEN	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
ZADEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALEN	Aluminum Platform

AFMONTAGE

SHIFTERS	Shimano Deore, LinkGlide
VOORDERAILLEUR	n/a
ACHTERDERAILLEUR	Shimano Deore LinkGlide, 10-speed, Shadow+
REMMEN	Shimano BR-MT200, hydraulic disc, 180mm
REMHENDELS	Shimano BL-MT201
CASSETTE	Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed
AANDRIJVING	Shimano LinkGlide, CN-LG500
CRANKSET	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
BOTTOM BRACKET	n/a

WIELSET

VELGEN	eX25, Tubeless Ready, 622x25 Aluminium
NAVEN	Giant eTracker, [F] 110x15 [R] 142x12
SPAKEN	Stainless steel, e-bike optimized
BANDEN	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready
EXTRA'S	KSA40 direct mount kickstand

ACCESSOIRES

VERLICHTING	Recon E HL50 StVZO [F]JAXA NYX 6-12V E-bike tail light with brake sensor [R]
SLOT	ABUS Xplus battery lock
DRAGER	MIK rack. System bag & basket compatible
SPATBORD/ KETTINGKAST	Alluminum Fenders

Adviesprijs: € 3.799,00

GEOMETRIE

FRAME	M	L	XL	XXL
Zitbuis lengte (mm)	435	485	535	585
Zitbuis hoek	73,0°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	600	610	630	650
Balhoofdbuis Lengte (mm)	140	155	170	185
Balhoofdbuis Hoek	69,5°	69,5°	69,5°	69,5°
Vork Sprong (mm)	51	51	51	51
Naloop (mm)	84	84	84	84
Wielbasis (mm)	1144	1155	1176	1197
Liggende achtervork lengte (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	668	682	696	710
Reach (mm)	396	401	417	433
Stand Over Height (mm)	759	793	824	856
Stuur breedte (mm)	690	690	690	690
Stuurpen Lengte (mm)	80	100	100	100
Cranklengte (mm)	170	170	170	170
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.