

# EXPLORE E+ 1 HEREN

**GIANT**



## SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	85Nm
BEDIENINGSUNIT	Giant RideControl Go 2 Giant RideControl Ergo4 Dual Remotes
DISPLAY	Geïntegreerd in het stuur
ACCU	800Wh
ACTIERADIUS	CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
LADER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	M, L, XL, XXL
KLEUREN	Metallic Navy
FRAME	Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VOORVORK	100mm travel 15x110mm
DEMPER	n/a
ONDERDELEN	
STUUR	Giant Contour Comfort Riser 31.8x720mm
HANDVATTEN	RideControl Ergo4 Integrated Trekking (w/Bar-end)
STUURPEN	Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm)
ZADELPEN	Giant Contact Switch Dropper Seatpost (100mm Travel)
ZADEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALEN	VPE-537 PP Platform Pedal
AFMONTAGE	
SHIFTERS	Shimano Cues Di2 E-Shift
ACHTERDERAILLEUR	Shimano Cues Di2, 11-Speed
REMMEN	Shimano Deore, BR-MT420, hydraulic disc, 4-piston, 203mm [F] 180mm [R]
REMHENDELS	Shimano BL-M401
CASSETTE	Shimano, 11-45T, 11-speed
AANDRIJVING	Shimano Linkglide CN-LG500
CRANKSET	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 42T

WIELSET	
VELGEN	622x25 Aluminium
NAVEN	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
SPAKEN	Stainless steel, e-bike optimized
BANDEN	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
EXTRA'S	Aegis Tire Checker
ACCESSOIRES	
VERLICHTING	Supernova Mini 3 [F] Rear Rack Integrated tail light [R]
SLOT	ABUS Xplus battery lock Shield Xplus ART 5755 R frame lock
DRAGER	MIK rack. System bag & basket compatible Tail light integrated Aegis Radar compatible
SPATBORD/ KETTINGKAST	Alluminum
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

Adviesprijs: € 4.699,00

## GEOMETRIE

FRAME	M	L	XL	XXL
Zitbuis lengte (mm)	435	485	535	585
Zitbuis hoek	73,0°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	600	610	630	650
Balhoofdbuis Lengte (mm)	140	155	170	185
Balhoofdbuis Hoek	69,5°	69,5°	69,5°	69,5°
Vork Sprong (mm)	51	51	51	51
Wielbasis (mm)	1144	1155	1176	1197
Liggende achtervork lengte (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	668	682	696	710
Reach (mm)	396	401	417	433
Stuur breedte (mm)	690	760	760	760
Stuurpen Lengte (mm)	80	100	100	100
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.