

EXPLORE E+ 1 STA



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	SyncDrive Sport 2, 75Nm, powered by Yamaha
OHJAYSYKSIKKÖ	Giant RideControl Dash, Smart Assist automatic mode, 5 support levels, USB-C (10W)
NÄYTTÖ	RideControl Dash, full color lcd screen
AKKU	EnergyPak Smart 625, EnergyPak Plus 250 range extender compatible
LATURI	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
YHTEYDET MUIHIN LAITTEISIIN	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RUNKO	
KOOT	S, M, L, XL
VÄRIT	Misty Forest , Cordovan
RUNKO	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
HAARUKKA	SR Suntour XCM34 LO, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
ISKUNVAIMENNIN	n/a
KOMONENTIT	
OHJAUSTANKO	Giant Connect Riser 31.8x690mm
GRIPIT	Giant Connect Ergo Max w/bar-end
OHJAINKANNATIN	Giant Contact (S/M: 80mm L/XL/XXL 100mm)
SATULATOLPPA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATULA	Selle Royal Vivo Ergo Moderate Unisex
POLKIMET	Aluminum Platform
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Deore, LinkGlide
ETUVAIHTAJA	n/a
TAKAVAIHTAJA	Shimano Deore LinkGlide, 10-speed, Shadow+
JARRUT	Shimano BR-MT200, hydraulic disc, 180mm
JARRUKAHVAT	Shimano BL-MT201
RATAPAKKA	Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed
KETJUT	Shimano LinkGlide, CN-LG500
KAMPISARJA	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
KESKIÖ	n/a

RENKAAT	
VANTEET	eX25, Tubeless Ready, 622x25 Aluminium
NAVAT	Giant eTracker, [F] 110x15 [R] 142x12
PINNAT	Stainless steel, e-bike optimized
RENKAAT	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready
LISÄTIEDOT	KSA40 direct mount kickstand
TARVIKKEET	
VALOT	Recon E HL50 StVZO [F]JAXA NYX 6-12V E-bike tail light with brake sensor [R]
LUKKO	ABUS Xplus battery lock
TAVARATELINE	MIK rack. System bag & basket compatible
KETJUNSUOJA	Alluminum Fenders

Suositus hinta: 3 939,00 €

GEOMETRIA

RUNKO	M	L
Satulaputken pituus (mm)	435	490
Satulaputken kulma	73,5°	73,0°
Vaakaputken pituus (mm)	600	610
Emäputken pituus (mm)	155	170
Emäputken kulma	69,5°	69,5°
Haarukan offset (mm)	51	51
Trail-mitta (mm)	84	84
Akseliväli (mm)	1151	1156
Takahaarukan alaputken pituus (mm)	470	470
Keskiön pudotus (mm)	60	60
Stack-mitta (mm)	682	696
Reach-mitta (mm)	398	397
Standover-mitta (mm)	670	650
Ohjaustangon leveys (mm)	690	690
Ohjainkannattimen pituus (mm)	80	100
Kammen pituus (mm)	170	170
Rengaskoko	29"	29"

Kaikki ilmoitettut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.