

EXPLORE E+ 1 STAGGER



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro 2, 85Nm, Powered by Yamaha
CONTROLLER	Giant RideControl Go 2 Giant RideControl Ergo 4 Remote
DISPLAY	RideDash Evo 2.0, full colour LCD screen
BATTERY	EnergyPak Smart 800Wh
CHARGER	EnergyPak 4A fast charger
MAXIMUM ASSISTED SPEED	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S
COLOURS	Metallic Navy
FRAME	ALUXX-Grade aluminium, disc, KSA40 kickstand compatible
FORK	SR Suntour XCR 34 2CR air boost 100mm travel 15x110mm thru axle
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contour Comfort Riser 31.8mm
GRIPS	RideControl Ergo 4 Integrated Trekking (w/Bar-end)
STEM	Giant Contour EVO integrated 16° (S/M:80mm L/XL 100mm)
SEATPOST	Giant Contact Switch travel-adjustable dropper, remote 70-100mm travel / 30.9 x 315mm
SADDLE	Selle Royal Vivo Ergo Moderate Unisex
PEDALS	Platform
DRIVETRAIN	
SHIFTERS	Shimano Cues Di2 E-Shift
REAR DERAILLEUR	Shimano Cues Di2, 11-Speed
BRAKES	Shimano MT420, hydraulic disc, RT64 [F]203mm, [R] 180mm
BRAKE LEVERS	Shimano BL-MT401
CASSETTE	Shimano Cues CS-LG40011 Linkglide, 11-45T, 11-speed
CHAIN	KMC e-glide EPT
CRANKSET	Forged alloy, steel 42T S:170mm, M:170mm, L:170mm, XL:170mm

WHEELS	
RIMS	Giant eX25, Tubeless Ready, Alloy
HUBS	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
SPOKES	Stainless steel, e-bike optimised
TYRES	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
EXTRAS	Aegis Tyre Pressure Management System (TPMS)
LIMITS	
NSW CERTIFICATION	ULL-104274-EA
ACCESSORIES	
LIGHTING	Supernova Mini 3 [F] Rear Rack Integrated tail light [R]
LOCK	ABUS Xplus battery lock
CARRIER	MIK rack. System bag & basket compatible Tail light integrated
FENDER/CHAINGUARD	Aluminium fenders
LIMITS	
COMBINED MAX LOAD LIMIT	156kg

Price: \$7,299.00

GEOMETRY

FRAME	S
Seat Tube Length (mm)	410
Seat Post Insertion Depth (mm)	260
Seat Tube Angle	74.0°
Top Tube Length (mm)	585
Head Tube Length (mm)	140
Head Tube Angle	69.0°
Fork Rake (mm)	51
Wheelbase (mm)	1147
Chain Stay Length (mm)	455
Bottom Bracket Drop (mm)	60
Stack (mm)	665
Reach (mm)	394
Stem Length (mm)	80
Wheel Size	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.