

EXPLORE E+ 1 STAGGER



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Sport 2, 75Nm, powered by Yamaha
BEDIENINGSUNIT	Giant RideControl Dash, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	RideControl Dash, full color lcd screen
ACCU	EnergyPak Smart 625, EnergyPak Plus 250 range extender compatible
LADER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	S, M, L, XL
KLEUREN	Misty Forest
FRAME	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VOORVORK	SR Suntour XCM34 LO, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
DEMPER	n/a
ONDERDELEN	
STUUR	Giant Connect Riser 31.8x690mm
HANDVATTEN	Giant Connect Ergo Max w/bar-end
STUURPEN	Giant Contact (S/M: 80mm L/XL/XXL 100mm)
ZADEL	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
ZADEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALEN	Aluminum Platform
AFMONTAGE	
SHIFTERS	Shimano Deore, LinkGlide
VOORDERAILLEUR	n/a
ACHTERDERAILLEUR	Shimano Deore LinkGlide, 10-speed, Shadow+
REMMEN	Shimano BR-MT200, hydraulic disc, 180mm
REMHENDELS	Shimano BL-MT201
CASSETTE	Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed
AANDRIJVING	Shimano LinkGlide, CN-LG500
CRANKSET	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
BOTTOM BRACKET	n/a

WIELSET	
VELGEN	eX25, Tubeless Ready, 622x25 Aluminium
NAVEN	Giant eTracker, [F] 110x15 [R] 142x12
SPAKEN	Stainless steel, e-bike optimized
BANDEN	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready
EXTRA'S	KSA40 direct mount kickstand
ACCESSOIRES	
VERLICHTING	Recon E HL50 StVZO [F]JAXA NYX 6-12V E-bike tail light with brake sensor [R]
SLOT	ABUS Xplus battery lock
DRAGER	MIK rack. System bag & basket compatible
SPATBORD/ KETTINGKAST	Alluminum Fenders

Adviesprijs: € 3.799,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis Lengte (mm)	410	435	490	545
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	585	600	610	630
Balhoofdbuis Lengte (mm)	140	155	170	185
Balhoofdbuis Hoek	69,0°	69,5°	69,5°	69,5°
Vork Sprong (mm)	51	51	51	51
Naloop (mm)	88	84	84	84
Wielbasis (mm)	1147	1151	1156	1177
Liggende achtervork lengte (mm)	455	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	665	682	696	710
Reach (mm)	394	398	397	413
Stand Over Height (mm)	682	670	650	649
Stuur breedte (mm)	690	690	690	690
Stuurpen Lengte (mm)	60	80	100	100
Cranklengte (mm)	170	170	170	170
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.