

EXPLORE E+ 1 STAGGER

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2, 85Nm PedalPlus 6-Sensor technology
BEDIENINGSUNIT	Giant RideControl Go 2 Giant RideControl Ergo4 Remote Left & Right
DISPLAY	Giant RideDash EVO 2.0, high-angle visibility, 3" full color LCD display, on-board navigation
ACCU	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible (exclude STA frame)
LADER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	S, M, L, XL
KLEUREN	Metallic Navy
FRAME	Gen 4 ALUXX aluminium, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VOORVORK	SR Suntour XCR34 2CR air boost 100mm travel 15x110mm AH axle
DEMPER	n/a
ONDERDELEN	
STUUR	Giant Contour Comfort Riser 31.8x720mm
HANDVATTEN	RideControl Ergo3 Integrated Trekking (w/Bar-end)
STUURPEN	Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm)
ZADELPEN	Giant Contact Switch Dropper Seatpost 100mm Travel
ZADEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALEN	Anti-slip Platform
AFMONTAGE	
SHIFTERS	Shimano Cues Di2 E-Shift
ACHTERDERAILLEUR	Shimano Cues Di2, 11-Speed
REMMEN	Shimano Deore, BR-MT420, hydraulic disc, 4-piston, 203mm [F] 180mm [R]
REMHENDELS	Shimano BL-M401
CASSETTE	Shimano, 11-45T, 11-speed
AANDRIJVING	Shimano Linkglide CN-LG500
CRANKSET	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 42T

WIELSET	
VELGEN	Giant eX25, Tubeless Ready, 622x25 Aluminium
NAVEN	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
SPAKEN	Stainless steel, e-bike optimized
BANDEN	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
EXTRA'S	Aegis Tire Checker
ACCESSOIRES	
VERLICHTING	Supernova Mini 3 [F] Rear Rack Integrated tail light [R]
SLOT	ABUS Xplus battery lock
DRAGER	MIK HD System rack. Child seat, bag & basket compatible
SPATBORD/ KETTINGKAST	Alluminum
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156kg

Adviesprijs: € 4.699,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis Lengte (mm)	410	435	490	545
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	585	600	610	630
Balhoofdbuis Lengte (mm)	140	155	170	185
Balhoofdbuis Hoek	69,0°	69,5°	69,5°	69,5°
Vork Sprong (mm)	51	51	51	51
Wielbasis (mm)	1147	1151	1156	1177
Liggende achtervork lengte (mm)	455	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	665	682	696	710
Reach (mm)	394	398	397	413
Stuur breedte (mm)	760	760	760	760
Stuurpen Lengte (mm)	80	80	100	100
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.