

EXPLORE E+ 2 DOUBLE DIAMOND

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
CONTROLLER	Giant RideControl Go 2 Giant RideControl Ergo4 Single Remote
DISPLAY	Giant RideDash EVO 2.0, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERY	Giant EnergyPak Smart 625Wh, Aluminium casing with highest safety standard (EN50604)
RANGE	CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	M, L, XL, XXL
COLORS	Alpine Green, Gray Dawn
FRAME	Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
FORK	SR Suntour XCR34 2CR coil boost 100mm travel 15x110mm AH axle
SHOCK	n/a
COMPONENTS	
HANDLEBAR	Giant Contour Comfort Riser 31.8x720mm
GRIPS	RideControl Ergo4 Integrated Trekking (w/Bar-end)
STEM	Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm)
SEATPOST	Giant Contact Switch Dropper Seatpost (100mm Travel)
SADDLE	Selle Royal Vivo Ergo Moderate Unisex
PEDALS	VPE-537 PP Platform Pedal
DRIVETRAIN	
SHIFTERS	Enviolo Pure
REAR DERAILLEUR	Enviolo Manual Modular 40T Spline
BRAKES	Shimano MT200, hydraulic disc, 180mm [F/R]
BRAKE LEVERS	Shimano BL-MT200
CASSETTE	Gates CDC stainless steel 22T rear sprocket
CHAIN	Gates CDC Carbon Drive 120T CenterTrack belt
CRANKSET	Forged alloy spider w/chainguard BCD 104, Gates CDC front sprocket 46T Forged aluminium crank arms

WHEELS	
RIMS	Giant eX25, Tubeless Ready, 622x25 Aluminium
HUBS	Giant eTracker 6-bolt disc 15x110mm [F] Enviolo Manual Modular 40T spline 6-bolt disc [R]
SPOKES	Stainless steel, e-bike optimized
TIRES	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
EXTRAS	Aegis Tire Checker
ACCESSORIES	
LIGHTING	Recon E HL 50 StVZO [F] Rear Rack Integrated tail light [R]
LOCK	ABUS Xplus battery lock
CARRIER	MIK rack. System bag & basket compatible Tail light integrated Aegis Radar compatible
FENDER/CHAINGUARD	Alluminum
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

GEOMETRY

FRAME	M	L	XL	XXL
Seat Tube Length (mm)	435	485	535	585
Seat Post Insertion Depth (mm)	260	260	260	260
Seat Tube Angle	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	600	610	630	650
Head Tube Length (mm)	140	155	170	185
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	51	51	51	51
Wheelbase (mm)	1144	1155	1176	1197
Chain Stay Length (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	668	682	696	710
Reach (mm)	396	401	417	433
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	80	100	100	100
Wheel Size	29"	29"	29"	29"

All specifications listed are subject to change without notice.