

EXPLORE E+ 2D GTS



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDrive Sport, 70Nm, powered by Yamaha
TIPALO	RideControl Ergo
PRIKAZOVALNIK	RideControl Dash
BATERIJA	EnergyPak Smart 500Wh EnergyPak Plus range extender compatible
OKVIR	
VELIKOSTI	S, M, L, XL, XXL
BARVE	Metallic Navy
OKVIR	ALUXX Aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
VILICE	SR Suntour NEX E25 NLO D5 63mm travel
AMORTIZER	-
KOMPONENTE	
KRMILO	Giant Connect Riser 31.8x690mm
GRIPS	Giant Contact Ergo Max Plus
OPORA KRMILA	Giant Contact
OPORA SEDEŽA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDEŽ	Selle Royal Vivo Ergo Moderate
PEDALA	Aluminum Platform
POGON	
PRESTAVNE ROČICE	Shimano Altus
PREDNJI MENJALNIK	-
ZADNJI MENJALNIK	Shimano Alivio, 9-speed
ZAVORE	Tektro HD-M275, hydraulic disc, 160/180mm
ZAVORNE ROČICE	Tektro HD-M275
VERIŽNIK	Shimano CS-HG200, 11-36T, 9-speed
VERIGA	KMC e.9 Sport, e-bike optimized
GONILKE Z VERIŽNIKI	Forged Alloy minimal Q-factor, 42T
BOTTOM BRACKET	-

OBROČNIKI	
OBROČI	Giant eX2, Tubeless Ready, 700c Aluminium
PESTA	Giant eTracker, [F] 100x9mm QR [R] 135mm QR
NAPERE	Stainless steel
PLAŠČI	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready, Reflex
DODATNA OPREMA	
SVETILA	Axa BlueLine 30Lux Steady E6 frontAxa BlueLine Steady E6 rear
PRTLJAŽNIK	MIK rack. System bag & basket compatible

GEOMETRIJA

OKVIR	S	M	L	XL	XXL
Dolžina sedežne cevi (mm)	435	485	535	585	610
Kot sedežne cevi	74,0°	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	570	590	610	630	650
Višina glave okvirja (mm)	130	140	155	170	185
Krmilni kot	69,5°	69,5°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	42	42	42	42	42
Trail (mm)	91,3	91,3	91,3	91,3	91,3
Medosna razdalja (mm)	1112	1121	1142	1163	1163
Dolžina cevi ob verigi (mm)	455	455	455	455	455
Bottom Bracket Drop (mm)	60	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	610	619	633	648	648
Doseg (mm)	395	400	416	432	432
Višina zgornje cevi (mm)	745	775	808	844	844
Širina krmila (mm)	690	690	690	690	690
Dolžina opore krmila (mm)	60	70	80	90	90
Dolžina gonilke (mm)	170	170	170	170	170
Velikost obročnikov	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.