

EXPLORE E+ 3 HEREN

GIANT



SPECIFICATIES

| HYBRID CYCLING TECHNOLOGY | |
|---------------------------|---|
| MOTOR | 75Nm |
| BEDIENINGSUNIT | Giant RideControl Go 2 Giant RideControl Ergo4 Single Remote |
| DISPLAY | Geïntegreerd in het stuur |
| ACCU | 625Wh |
| ACTIERADIUS | CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible |
| LADER | Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h |
| CONNECTIVITY | Giant RideControl App enabled ANT+ wireless display signal with e-bike profile |
| FRAME | |
| MATEN | M, L, XL, XXL |
| KLEUREN | Pyrite Brown |
| FRAME | Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount |
| VOORVORK | 100mm travel 15x110mm |
| DEMPER | n/a |
| ONDERDELEN | |
| STUUR | Giant Contour Comfort Riser 31.8x720mm |
| HANDVATTEN | RideControl Ergo4 Integrated Trekking (w/Bar-end) |
| STUURPEN | Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm) |
| ZADEL | Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium |
| ZADEL | Selle Royal Vivo Ergo Moderate Unisex |
| PEDALEN | VPE-537 PP Platform Pedal |
| AFMONTAGE | |
| SHIFTERS | Shimano Deore Linkglide |
| ACHTERDERAILLEUR | Shimano Deore Linkglide 10-speed |
| REMMEN | Tektro HD-M280, hydraulic disc, 180mm |
| REMHENDELS | Tektro HD-M280 |
| CASSETTE | Shimano Linkglide, 11-43T, 10-speed |
| AANDRIJVING | Shimano Linkglide CN-LG500 |
| CRANKSET | Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 42T |

| WIELSET | |
|-----------------------------|---|
| VELGEN | 622x25 Aluminium |
| NAVEN | Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R] |
| SPAKEN | Stainless steel, e-bike optimized |
| BANDEN | Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip |
| EXTRA'S | Aegis Tire Checker |
| ACCESSOIRES | |
| VERLICHTING | Recon E HLS0 StVZO [F] Rear Rack Integrated tail light [R] |
| SLOT | ABUS Xplus battery lock Shield Xplus ART 5755 R frame lock |
| DRAGER | MIK rack. System bag & basket compatible Tail light integrated Aegis Radar compatible |
| SPATBORD/ KETTINGKAST | Alluminum |
| LIMITS | |
| COMBINED MAXIMUM LOAD LIMIT | Type 3 150kg |

Adviesprijs: € 3.699,00

GEOMETRIE

| FRAME | M | L | XL | XXL |
|---------------------------------|-------|-------|-------|-------|
| Zitbuis lengte (mm) | 485 | 535 | 585 | 610 |
| Zitbuis hoek | 73,0° | 73,0° | 73,0° | 73,0° |
| Frame Lengte (horizontaal) (mm) | 590 | 610 | 630 | 650 |
| Balhoofdbuis Lengte (mm) | 140 | 155 | 170 | 185 |
| Balhoofdbuis Hoek | 69,5° | 69,5° | 69,5° | 69,5° |
| Vork Sprong (mm) | 42 | 42 | 42 | 42 |
| Wielbasis (mm) | 1121 | 1142 | 1163 | 1163 |
| Liggende achtervork lengte (mm) | 455 | 455 | 455 | 455 |
| Bottom Bracket Drop (mm) | 60 | 60 | 60 | 60 |
| Stack (mm) | 619 | 633 | 648 | 648 |
| Reach (mm) | 400 | 416 | 432 | 432 |
| Stand Over Height (mm) | 775 | 808 | 844 | 844 |
| Stuur breedte (mm) | 690 | 690 | 690 | 690 |
| Stuurpen Lengte (mm) | 70 | 80 | 90 | 90 |
| Wielmaat | 700C | 700C | 700C | 700C |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.