EXPLORE E+ 3 HEREN

SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
BEDIENINGSUNIT	Giant RideControl Go 2 Giant RideControl Ergo4 Single Remote
DISPLAY	Giant RideDash EVO 2.0, high-angle visibility, 3" full color LCD display, on-board navigation
ACCU	Giant EnergyPak Smart 625Wh, Aluminium casing with highest safety standard (EN50604)
ACTIERADIUS	CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
LADER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	M, L, XL, XXL
KLEUREN	Pyrite Brown
FRAME	Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VOORVORK	SR Suntour XCR34 2CR coil boost 100mm travel 15x110mm AH axle
DEMPER	n/a
ONDERDELEN	
STUUR	Giant Contour Comfort Riser 31.8x720mm
HANDVATTEN	RideControl Ergo4 Integrated Trekking (w/Bar-end)
STUURPEN	Giant Contour EVO integrated 16^0 NEW (S/M:80mm L/XL/XXL 100mm)
ZADELPEN	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
ZADEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALEN	VPE-537 PP Platform Pedal
AFMONTAGE	
SHIFTERS	Shimano Deore Linkglide
ACHTERDERAILLEUR	Shimano Deore Linkglide 10-speed
REMMEN	Tektro HD-M280, hydraulic disc, 180mm
REMHENDELS	Tektro HD-M280
CASSETTE	Shimano Linkglide, 11-43T, 10-speed
AANDRIJVING	Shimano Linkglide CN-LG500
CRANKSET	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 42T

WIELSET	
VELGEN	Giant eX25, Tubeless Ready, 622x25 Aluminium
NAVEN	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
SPAKEN	Stainless steel, e-bike optimized
BANDEN	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
EXTRA'S	Aegis Tire Checker
ACCESSORES	
VERLICHTING	Recon E HL50 StVZO [F] Rear Rack Integrated tail light [R]
SLOT	ABUS Xplus battery lock Shield Xplus ART 5755 R frame lock
DRAGER	MIK rack. System bag & basket compatible Tail light integrated Aegis Radar compatible
SPATBORD/ KETTINGKAST	Alluminum
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

Adviesprijs: € 3.699,00

GEOMETRIE

FRAME	M	L	XL	XXL
Zitbuis Lengte (mm)	485	535	585	610
Zitbuis Hoek	73,0°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	590	610	630	650
Balhoofdbuis Lengte (mm)	140	155	170	185
Balhoofdbuis Hoek	69,5°	69,5°	69,5°	69,5°
Vork Sprong (mm)	42	42	42	42
Wielbasis (mm)	1121	1142	1163	1163
Liggende achtervork lengte (mm)	455	455	455	455
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	619	633	648	648
Reach (mm)	400	416	432	432
Stand Over Height (mm)	775	808	844	844
Stuur breedte (mm)	690	690	690	690
Stuurpen Lengte (mm)	70	80	90	90
Wielmaat	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.