

EXPLORE E+ 3 PRO DOUBLE DIAMOND

GIANT



SPECS

HYBRID SYKKEL TEKNOLOGI	
MOTOR	Giant SyncDrive Pro2, 85Nm PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Go 2 Giant RideControl Ergo4 Single Remote
DISPLAY	Giant RideDash EVO 2.0, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERI	Giant EnergyPak Smart 625Wh, Aluminium casing with highest safety standard (EN50604)
REKKEVIDDE	CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RAMME	
STØRRELSE	M, L, XL, XXL
FARGE	Pyrite Brown, Terracotta Merck
RAMME	Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
GAFFEL	SR Suntour XCR34 2CR coil boost 100mm travel 15x110mm AH axle
DEMPER	n/a
KOMPONENTER	
STYRE	Giant Contour Comfort Riser 31.8x720mm
GRIPS	RideControl Ergo4 Integrated Trekking (w/Bar-end)
STYRSTEM	Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm)
SETEPINNE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALER	VPE-537 PP Platform Pedal
DRIVVERK	
GIRHENDLER	Shimano Deore Linkglide
BAKGIR	Shimano Deore Linkglide 10-speed
BREMSER	Tektro HD-M280, hydraulic disc, 180mm
BREMSEHENDLER	Tektro HD-M280
KASSETT	Shimano Linkglide, 11-43T, 10-speed
KJEDE	Shimano Linkglide CN-LG500
KRANK	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 42T

HJUL	
FELG	Giant eX25, Tubeless Ready, 622x25 Aluminium
NAV	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
EIKE	Stainless steel, e-bike optimized
DEKK	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
EXTRAS	Aegis Tire Checker
TILBEHØR	
LYS	Recon E HL50 StVZO [F] Rear Rack Integrated tail light [R]
LÅS	ABUS Xplus battery lock
BAGASJEBRETT	MIK rack. System bag & basket compatible Tail light integrated Aegis Radar compatible
SKJERMER/KJEDEBESKYTTER	Alluminum
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

GEOMETRI

RAMME	M	L	XL	XXL
Seat Tube Length (mm)	435	485	535	585
Seat Post Insertion Depth (mm)	260	260	260	260
Seat Tube Angle	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	600	610	630	650
Head Tube Length (mm)	140	155	170	185
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	51	51	51	51
Wheelbase (mm)	1144	1155	1176	1197
Chain Stay Length (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	668	682	696	710
Reach (mm)	396	401	417	433
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	80	100	100	100
Wheel Size	29"	29"	29"	29"

Alle spesifikasjonene kan endres uten varsel.