

EXPLORE E+ 3 PRO DOUBLE DIAMOND **GIANT**



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2, 85Nm PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Go 2 Giant RideControl Ergo4 Single Remote
DISPLAY	Giant RideDash EVO 2.0, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERY	Giant EnergyPak Smart 625Wh, Aluminium casing with highest safety standard (EN50604)
RANGE	CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRU	
MARIMI	M, L, XL, XXL
CULORI	Pyrite Brown, Terracotta Merck
CADRU	Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
FURCA	SR Suntour XCR34 2CR coil boost 100mm travel 15x110mm AH axle
SOC	n/a
COMPONENTE	
GHIDON	Giant Contour Comfort Riser 31.8x720mm
GRIPS	RideControl Ergo4 Integrated Trekking (w/Bar-end)
PIPA	Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm)
TIJA SA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SA	Selle Royal Vivo Ergo Moderate Unisex
PEDALE	VPE-537 PP Platform Pedal
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano Deore Linkglide
SCHIMBATOR SPATE	Shimano Deore Linkglide 10-speed
FRANE	Tektro HD-M280, hydraulic disc, 180mm
MANETE FRANA	Tektro HD-M280
PINIOANE	Shimano Linkglide, 11-43T, 10-speed
LANT	Shimano Linkglide CN-LG500
ANGRENAJ	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 42T

ROTI	
JANTE	Giant eX25, Tubeless Ready, 622x25 Aluminium
BUTUCI	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
SPITE	Stainless steel, e-bike optimized
ANVELOPE	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
EXTRAS	Aegis Tire Checker
ACCESSORIES	
LIGHTING	Recon E HL50 StVZO [F] Rear Rack Integrated tail light [R]
LOCK	ABUS Xplus battery lock
CARRIER	MIK rack. System bag & basket compatible Tail light integrated Aegis Radar compatible
FENDER/CHAINGUARD	Alluminum
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

GEOMETRIE

CADRU	M	L	XL	XXL
Seat Tube Length (mm)	435	485	535	585
Seat Tube Angle	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	600	610	630	650
Head Tube Length (mm)	140	155	170	185
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	51	51	51	51
Wheelbase (mm)	1144	1155	1176	1197
Chain Stay Length (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	668	682	696	710
Reach (mm)	396	401	417	433
Handlebar Width (mm)	690	760	760	760
Stem Length (mm)	80	100	100	100
Wheel Size	29"	29"	29"	29"

Toate specificatiile enumerate se pot schimba fara notificare prealabila.