

# EXPLORE E+ 3 PRO STAGGER

**GIANT**



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	Giant SyncDrive Pro2, 85Nm PedalPlus 6-Sensor technology
<b>SENSOR</b>	Giant RideControl Go 2 Giant RideControl Ergo4 Single Remote
<b>DISPLAY</b>	Giant RideDash EVO 2.0, high-angle visibility, 3" full color LCD display, on-board navigation
<b>BATTERY</b>	Giant EnergyPak Smart 625Wh, Aluminium casing with highest safety standard (EN50604)
<b>RANGE</b>	CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
<b>CHARGER</b>	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRU	
<b>MARIMI</b>	S, M, L, XL
<b>CULORI</b>	Pyrite Brown, Terracotta Merck
<b>CADRU</b>	Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
<b>FURCA</b>	SR Suntour XCR34 2CR coil boost 100mm travel 15x110mm AH axle
<b>SOC</b>	n/a
COMPONENTE	
<b>GHIDON</b>	Giant Contour Comfort Riser 31.8x720mm
<b>GRIPS</b>	RideControl Ergo4 Integrated Trekking (w/Bar-end)
<b>PIPA</b>	Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm)
<b>TIJA SA</b>	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
<b>SA</b>	Selle Royal Vivo Ergo Moderate Unisex
<b>PEDALE</b>	VPE-537 PP Platform Pedal
SISTEMUL DE SCHIMBARE A VITEZELOR	
<b>MANETE SCHIMBATOR</b>	Shimano Deore Linkglide
<b>SCHIMBATOR SPATE</b>	Shimano Deore Linkglide 10-speed
<b>FRANE</b>	Tektro HD-M280, hydraulic disc, 180mm
<b>MANETE FRANA</b>	Tektro HD-M280
<b>PINIOANE</b>	Shimano Linkglide, 11-43T, 10-speed
<b>LANT</b>	Shimano Linkglide CN-LG500
<b>ANGRENAJ</b>	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 42T

ROTI	
<b>JANTE</b>	Giant eX25, Tubeless Ready, 622x25 Aluminium
<b>BUTUCI</b>	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
<b>SPITE</b>	Stainless steel, e-bike optimized
<b>ANVELOPE</b>	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
<b>EXTRAS</b>	Aegis Tire Checker
ACCESSORIES	
<b>LIGHTING</b>	Recon E HL50 StVZO [F] Rear Rack Integrated tail light [R]
<b>LOCK</b>	ABUS Xplus battery lock
<b>CARRIER</b>	MIK rack. System bag & basket compatible Tail light integrated Aegis Radar compatible
<b>FENDER/CHAINGUARD</b>	Alluminum
LIMITS	
<b>COMBINED MAXIMUM LOAD LIMIT</b>	Type 3 150kg

## GEOMETRIE

CADRU	S	M	L	XL
Seat Tube Length (mm)	410	435	490	545
Seat Tube Angle	74,0°	73,5°	73,0°	73,0°
Top Tube Length (mm)	585	600	610	630
Head Tube Length (mm)	140	155	170	185
Head Tube Angle	69,0°	69,5°	69,5°	69,5°
Fork Rake (mm)	51	51	51	51
Wheelbase (mm)	1147	1151	1156	1177
Chain Stay Length (mm)	455	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	665	682	696	710
Reach (mm)	394	398	397	413
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	80	80	100	100
Wheel Size	29"	29"	29"	29"

Toate specificatiile enumerate se pot schimba fara notificare prealabila.