

EXPLORE E+ 3 STAGGER

GIANT

SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Go 2 Giant RideControl Ergo4 Single Remote
PRIKAZ	Giant RideDash EVO 2.0, high-angle visibility, 3" full color LCD display, on-board navigation
BATERIJA	Giant EnergyPak Smart 625Wh, Aluminium casing with highest safety standard (EN50604)
AUTONOMIJA / DOMET	CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIČINE	S, M, L, XL
BOJE	Pyrite Brown, Terracotta Merck
OKVIR	Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VILICA	SR Suntour XCR34 2CR coil boost 100mm travel 15x110mm AH axle
AMORTIZER	n/a
KOMPONENTE	
VOLAN	Giant Contour Comfort Riser 31.8x720mm
GRIPS	RideControl Ergo4 Integrated Trekking (w/Bar-end)
LULA VOLANA	Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm)
CIJEV SJEDALA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SJEDALO	Selle Royal Vivo Ergo Moderate Unisex
PEDALE	VPE-537 PP Platform Pedal
POGON	
RUČICE MJENJAČA	Shimano Deore Linkglide
STRAŽNJI MJENJAČ	Shimano Deore Linkglide 10-speed
KOČNICE	Tektro HD-M280, hydraulic disc, 180mm
RUČICE KOČNICA	Tektro HD-M280
KAZETA	Shimano Linkglide, 11-43T, 10-speed
LANAC	Shimano Linkglide CN-LG500
POGON	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 42T

KOTAČI	
OBRUČI	Giant eX25, Tubeless Ready, 622x25 Aluminium
NABE	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
ŽBICE	Stainless steel, e-bike optimized
GUME	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
DODACI	Aegis Tire Checker
DODACI	
SVJETLA	Recon E HL50 StVZO [F] Rear Rack Integrated tail light [R]
LOKOTI	ABUS Xplus battery lock
NOSAČ	MIK rack. System bag & basket compatible Tail light integrated Aegis Radar compatible
BLATOBRA NI / ŠTITNIK LANCA	Alluminum
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

GEOMETRIJA

OKVIR	S	M	L	XL
Dužina cijevi sjedala (mm)	410	435	490	545
Kut cijevi sjedala	74,0°	73,5°	73,0°	73,0°
Dužina gornje cijevi (mm)	585	600	610	630
Dužina prednje cijevi (mm)	140	155	170	185
Kut vilice	69,0°	69,5°	69,5°	69,5°
Zakrivljenost vilice (offset) (mm)	51	51	51	51
Međuosovinski razmak kotača (mm)	1147	1151	1156	1177
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	455	470	470	470
Položaj osovine pogona (mm)	60	60	60	60
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	665	682	696	710
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	394	398	397	413
Širina volana (mm)	760	760	760	760
Dužina lule volana (mm)	80	80	100	100
Veličina kotača	29"	29"	29"	29"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.