

EXPLORE E+ 3 STAGGER

GIANT



SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Go 2 Giant RideControl Ergo4 Single Remote
ECRÃ	Giant RideDash EVO 2.0, high-angle visibility, 3" full color LCD display, on-board navigation
BATERIA	Giant EnergyPak Smart 625Wh, Aluminium casing with highest safety standard (EN50604)
AUTONOMIA	CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CARREGADOR	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
QUADRO	
TAMANHOS	S, M, L, XL
CORES	Pyrite Brown
QUADRO	Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
FORQUILHA	SR Suntour XCR34 2CR coil boost 100mm travel 15x110mm AH axle
AMORTECEDORES	n/a
COMPONENTES	
GUIADOR	Giant Contour Comfort Riser 31.8x720mm
PUNHOS	RideControl Ergo4 Integrated Trekking (w/Bar-end)
AVANÇO	Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm)
ESPIGÃO DE SELIM	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELIM	Selle Royal Vivo Ergo Moderate Unisex
PEDAIS	VPE-537 PP Platform Pedal
TRANSMISSÃO	
MANETES	Shimano Deore Linkglide
DESVIADOR TRASEIRO	Shimano Deore Linkglide 10-speed
TRAVÕES	Tektro HD-M280, hydraulic disc, 180mm
MANÍPULOS DOS TRAVÕES	Tektro HD-M280
CASSETTE	Shimano Linkglide, 11-43T, 10-speed
CORRENTE	Shimano Linkglide CN-LG500
CONJUNTO PEDALEIRO	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 42T

RODAS	
AROS	Giant eX25, Tubeless Ready, 622x25 Aluminium
CUBOS	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
RAIOS	Stainless steel, e-bike optimized
PNEUS	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
EXTRAS	Aegis Tire Checker
ACESSÓRIOS	
LUZES	Recon E HL50 StVZO [F] Rear Rack Integrated tail light [R]
CADEADO	ABUS Xplus battery lock
PORTA-BICICLETAS	MIK rack. System bag & basket compatible Tail light integrated Aegis Radar compatible
GUARDA LAMAS/PROTECTOR DE CORRENTE	Alluminum
LIMITES	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

Preço: 3 149,00 €

GEOMETRIA

QUADRO	S	M
Comprimento do tubo do assento (mm)	435	485
Ângulo do tubo do assento	73,0°	73,0°
Comprimento do tubo superior (mm)	570	590
Comprimento do tubo principal (mm)	130	140
Ângulo do tubo principal	69,5°	69,5°
Garfo ancinho (mm)	42	42
distância entre eixos (mm)	1112	1121
Comprimento Chain Stay (mm)	455	455
Suporte inferior (mm)	60	60
Pilha (mm)	609	618
Alcãçar (mm)	383	401
Altura do standover (mm)	682	676
Largura do guidão (mm)	690	690
Comprimento da haste (mm)	60	70
Tamanho da roda	700C	700C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.