

EXPLORE E+ 3 STAGGER

GIANT



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
TIPALO	Giant RideControl Go 2 Giant RideControl Ergo4 Single Remote
PRIKAZOVALNIK	Giant RideDash EVO 2.0, high-angle visibility, 3" full color LCD display, on-board navigation
BATERIJA	Giant EnergyPak Smart 625Wh, Aluminium casing with highest safety standard (EN50604)
DOSEG	CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Pyrite Brown, Terracotta Merck
OKVIR	Gen 4 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VILICE	SR Suntour XCR34 2CR coil boost 100mm travel 15x110mm AH axle
AMORTIZER	n/a
KOMPONENTE	
KRMILO	Giant Contour Comfort Riser 31.8x720mm
GRIPS	RideControl Ergo4 Integrated Trekking (w/Bar-end)
OPORA KRMILA	Giant Contour EVO integrated 16° NEW (S/M:80mm L/XL/XXL 100mm)
OPORA SEDEŽA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDEŽ	Selle Royal Vivo Ergo Moderate Unisex
PEDALA	VPE-537 PP Platform Pedal
POGON	
PRESTAVNE ROČICE	Shimano Deore Linkglide
ZADNJI MENJALNIK	Shimano Deore Linkglide 10-speed
ZAVORE	Tektro HD-M280, hydraulic disc, 180mm
ZAVORNE ROČICE	Tektro HD-M280
VERIŽNIK	Shimano Linkglide, 11-43T, 10-speed
VERIGA	Shimano Linkglide CN-LG500
GONILKE Z VERIŽNIKI	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 42T

OBROČNIKI	
OBROČI	Giant eX25, Tubeless Ready, 622x25 Aluminium
PESTA	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
NAPERE	Stainless steel, e-bike optimized
PLAŠČI	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready, w/ Reflection Strip
DODATKI	Aegis Tire Checker
DODATNA OPREMA	
SVETILA	Recon E HL50 StVZO [F] Rear Rack Integrated tail light [R]
KLJUČAVNICA	ABUS Xplus battery lock
PRTLJAŽNIK	MIK rack. System bag & basket compatible Tail light integrated Aegis Radar compatible
BLATNIKI/ŠČITNIK VERIGE	Alluminum
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	410	435	490	545
Kot sedežne cevi	74,0°	73,5°	73,0°	73,0°
Top Tube Length (mm)	585	600	610	630
Višina glave okvirja (mm)	140	155	170	185
Krmilni kot	69,0°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	51	51	51	51
Medosna razdalja (mm)	1147	1151	1156	1177
Dolžina cevi ob verigi (mm)	455	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	665	682	696	710
Doseg (mm)	394	398	397	413
Širina krmila (mm)	760	760	760	760
Dolžina opore krmila (mm)	80	80	100	100
Velikost obročnikov	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.