

EXPLORE E+ 4 DOUBLE DIAMOND

GIANT

SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
SENSOR	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
PRIKAZ	Giant RideControl Dash 2 high-angle visibility, full color LCD display
BATERIJA	Giant EnergyPak Smart 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIČINE	M, L, XL, XXL
BOJE	Stealth Chome, Mars Dust
OKVIR	Gen 3 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VILICA	SR Suntour XCM34 Boost DS 100mm travel 15AH4-110 axle
AMORTIZER	n/a
KOMPONENTE	
VOLAN	Giant Connect Riser 31.8x690mm
GRIPS	Giant Contact
LULA VOLANA	Giant Contour integrated 16° (S/M:80mm L/XL/XXL 100mm)
CIJEV SJEDALA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SJEDALO	Selle Royal Vivo Ergo Moderate Unisex
PEDALE	Anti-slip Platform Pedal
POGON	
RUČICE MJENJAČA	Shimano Cues
STRAŽNJI MJENJAČ	Shimano Cues 9-speed
KOČNICE	Tektro HD-M280, hydraulic disc, 180mm
RUČICE KOČNICA	Tektro HD-M280
KAZETA	Shimano Cues, 11-36T, 9-speed
LANAC	Shimano Linkglide CN-LG500
POGON	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 46T

KOTAČI	
OBRUČI	Giant GX03V, 622x21 Aluminium
NABE	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
ŽBICE	Stainless steel, e-bike optimized
GUME	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready,w/ Reflection Strip
DODACI	Aegis Tire Checker
DODACI	
SVJETLA	Recon E HL50 StVZO [F] AXA NYX 6-12V E-bike tail light [R]
LOKOTI	ABUS Xplus battery lock
NOSAČ	MIK rack. System bag & basket compatible
BLATOBRAANI / ŠTITNIK LANCA	Alluminum
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	Type 3 150kg

GEOMETRIJA

OKVIR	S	M	L	XL	XXL
Dužina cijevi sjedala (mm)	435	485	535	585	610
Kut cijevi sjedala	74,0°	73,0°	73,0°	73,0°	73,0°
Dužina gornje cijevi (mm)	570	590	610	630	650
Dužina prednje cijevi (mm)	130	140	155	170	185
Kut vilice	69,5°	69,5°	69,5°	69,5°	69,5°
Zakrivljenost vilice (offset) (mm)	42	42	42	42	42
Međuosovinski razmak kotača (mm)	1112	1121	1142	1163	1163
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	455	455	455	455	455
Položaj osovine pogona (mm)	60	60	60	60	60
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	610	619	633	648	648
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	395	400	416	432	432
Prekoračna visina (mm)	745	775	808	844	844
Širina volana (mm)	690	690	690	690	690
Dužina lule volana (mm)	60	70	80	90	90
Veličina kotača	700C	700C	700C	700C	700C

Sve navedene specifikacije podložne su promjeni bez prethodne najave.