

# EXPLORE E+ 4 DOUBLE DIAMOND



## SPECS

### HYBRID CYCLING TECHNOLOGY

<b>MOTOR</b>	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
<b>SENSOR</b>	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
<b>DISPLAY</b>	Giant RideControl Dash 2 high-angle visibility, full color LCD display
<b>BATTERY</b>	Giant EnergyPak Smart 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
<b>CHARGER</b>	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile

### CADRU

<b>MARIMI</b>	M, L, XL, XXL
<b>CULORI</b>	Stealth Chome, Mars Dust
<b>CADRU</b>	Gen 3 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
<b>FURCA</b>	SR Suntour XCM34 Boost DS 100mm travel 15AH4-110 axle
<b>SOC</b>	n/a

### COMPONENTE

<b>GHIDON</b>	Giant Connect Riser 31.8x690mm
<b>GRIPS</b>	Giant Contact
<b>PIPA</b>	Giant Contour integrated 16° (S/M:80mm L/XL/XXL 100mm)
<b>TIJA SA</b>	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
<b>SA</b>	Selle Royal Vivo Ergo Moderate Unisex
<b>PEDALE</b>	Anti-slip Platform Pedal

### SISTEMUL DE SCHIMBARE A VITEZELOR

<b>MANETE SCHIMBATOR</b>	Shimano Cues
<b>SCHIMBATOR SPATE</b>	Shimano Cues 9-speed
<b>FRANE</b>	Tektro HD-M280, hydraulic disc, 180mm
<b>MANETE FRANA</b>	Tektro HD-M280
<b>PINIOANE</b>	Shimano Cues, 11-36T, 9-speed
<b>LANT</b>	Shimano Linkglide CN-LG500
<b>ANGRENAJ</b>	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 46T

### ROTI

<b>JANTE</b>	Giant GX03V, 622x21 Aluminium
<b>BUTUCI</b>	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
<b>SPITE</b>	Stainless steel, e-bike optimized
<b>ANVELOPE</b>	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready,w/ Reflection Strip
<b>EXTRAS</b>	Aegis Tire Checker

### ACCESSORIES

<b>LIGHTING</b>	Recon E HL50 StVZO [F] AXA NYX 6-12V E-bike tail light [R]
<b>LOCK</b>	ABUS Xplus battery lock
<b>CARRIER</b>	MIK rack. System bag & basket compatible
<b>FENDER/CHAINGUARD</b>	Alluminum

### LIMITS

<b>COMBINED MAXIMUM LOAD LIMIT</b>	Type 3 150kg
------------------------------------	--------------

## GEOMETRIE

CADRU	S	M	L	XL	XXL
Seat Tube Length (mm)	435	485	535	585	610
Seat Tube Angle	74,0°	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	570	590	610	630	650
Head Tube Length (mm)	130	140	155	170	185
Head Tube Angle	69,5°	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	42	42	42	42	42
Wheelbase (mm)	1112	1121	1142	1163	1163
Chain Stay Length (mm)	455	455	455	455	455
Bottom Bracket Drop (mm)	60	60	60	60	60
Stack (mm)	610	619	633	648	648
Reach (mm)	395	400	416	432	432
Stand Over Height (mm)	745	775	808	844	844
Handlebar Width (mm)	690	690	690	690	690
Stem Length (mm)	60	70	80	90	90
Wheel Size	700C	700C	700C	700C	700C

Toate specificatiile enumerate se pot schimba fara notificare prealabila.