

EXPLORE E+ 4 STA

GIANT



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
COMMANDE	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
ECRAN	Giant RideControl Dash 2 high-angle visibility, full color LCD display
BATTERIE	Giant EnergyPak Smart 500Wh, Aluminium casing with highest safety standard (EN50604)
ENERGYPAK PLUS COMPATIBLES	CO2 Neutral production EnergyPak Plus 250 compatible (except XS & S sizes)
CHARGEUR	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITÉ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile, E-Lock, FindMyBike, compatible Tire Checker Aegis
CADRE	
TAILLES	S, M, L, XL
COLORIS	Stealth Chome
CADRE	Gen 3 ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
FOURCHE	SR Suntour XCM34 Boost DS 100mm travel 15AH4-110 axle
AMORTISSEUR	n/a
COMPOSANTS	
CINTRE	Giant Connect Riser 31.8x690mm
POIGNÉES	Giant Contact
POTENCE	Giant Contour integrated 16° (S/M:80mm L/XL/XXL 100mm)
TIGE DE SELLE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELLE	Selle Royal Vivo Ergo Moderate Unisex
PÉDALES	Anti-slip Platform Pedal
DÉRAILLEUR	
MANETTES	Shimano Cues
DÉRAILLEUR ARRIÈRE	Shimano Cues 9-speed
FREINS	Tektro HD-M280, hydraulic disc, 180mm
LEVIERS DE FREIN	Tektro HD-M280
CASSETTE	Shimano Cues, 11-36T, 9-speed
CHAÎNE	Shimano Linkglide CN-LG500
PÉDALIER	Forged alloy spider w/chainguard BCD 104, steel narrow/wide chainring 46T

ROUES	
JANTES	Giant GX03V, 622x21 Aluminium
MOYEUX	Giant eTracker Boost 6-bolt disc 15x110mm [F] 12x148mm [R]
RAYONS	Stainless steel, e-bike optimized
PNEUS	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready,w/ Reflection Strip
EXTRAS	Aegis Tire Checker
ACCESSOIRES	
ECLAIRAGE	Recon E HL50 StVZO [F] AXA NYX 6-12V E-bike tail light [R]
ANTI-VOL	ABUS Xplus battery lock
PORTE-BAGAGES	MIK rack. System bag & basket, aegis radar compatible
GARDE-BOUE / CHAÎNE	Alluminum
LIMITES	
POIDS TOTAL MAX AUTORISÉ	Type 3 150kg

Prix Public Conseillé: 2 800,00 €

GÉOMÉTRIE

CADRE	S	M	L
Longueur de tube de selle (mm)	435	485	535
Angle de tube de selle	73,0°	73,0°	73,0°
Longueur du tube supérieur (mm)	570	590	610
Longueur du tube de direction (mm)	130	140	155
Angle du tube de direction	69,5°	69,5°	69,5°
Déport de fourche (mm)	42	42	42
Empattement (mm)	1112	1121	1142
Longueur des bases (mm)	455	455	455
Drop du boîtier de pédalier (mm)	60	60	60
Stack (mm)	609	618	633
Reach (mm)	383	401	416
Hauteur en statique (mm)	682	676	665
Largeur de cintre (mm)	690	690	690
Longueur de potence (mm)	60	70	80
Diamètre des roues	700C	700C	700C

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.